

MASTER TL5 High Efficiency Secura

MASTER TL5 HE Secura 14W/840 UNP/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope and protective coating around the lamp to prevent contamination resulting from breakage

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- It's strongly recommended to replace Secura lamps before or at the moment the specified lamp life (50% failures @ 3 hrs switching cycle) is reached.

Product data

General Information	
Cap-Base	G5 [G5]

Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	1,350 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	86 lm/W
Color rendering index (CRI)	82

Operating and Electrical	
Power Consumption	14.0 W
Lamp Current (Nom)	0.165 A

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Shape	T5 [16 mm (T5)]

Approval and Application	
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	15 kWh


Product Data	
Order product name	MASTER TL5 HE Secura 14W/840 UNP/40
Full product name	MASTER TL5 HE Secura 14W/840 UNP/40
Full product code	871150095476355
Order code	95476355

MASTER TL5 High Efficiency Secura

Material Nr. (12NC)	927926184018
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500954763
Numerator - Packs per outer box	40


EAN/UPC - Case	8711500954770

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE Secura 14W/840 UNP/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm

Photometric data




Spectral Power Distribution Colour - MASTER TL5 HE Secura 14W/840 UNP/40

Lifetime




Life Expectancy Diagram - MASTER TL5 HE Secura 14W/840 UNP/40



Life Expectancy Diagram - MASTER TL5 HE Secura 14W/840 UNP/40

MASTER TL5 High Efficiency Secura

Lifetime



Lumen Maintenance Diagram - MASTER TL5 HE Secura 14W/840 UNP/40

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.