

# Lighting

**PHILIPS** 

# TL5 Essential HE Super 80

## TL5 Essential 28W/830 1SL/40

Philips TL5 Essential Super80 is a new fluorescent lamp which provides home users and professional end-users an aesthetic miniaturized lighting solution with high reliability at low price.

#### Warnings and Safety

• 20,000 hours lifetime (50% survival point, 3 hour cycle) with preheat ballast which is ENEC compliant. Lifetime performance may differ on non-ENEC compliant ballasts.

#### **Product data**


General Information			
Cap-Base	G5		
Nominal lifetime	15,000 hour(s)		
Light Technical			
Color Code	830 [CCT of 3000K]		
Luminous Flux	2,900 lm		
Color Designation	Warm White (WW)		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	94 lm/W		
Color rendering index (CRI)	82		
Operating and Electrical			
Power Consumption	27.8 W		
Lamp Current (Nom)	0.170 A		

No			
Т5			
2.0 mg			
31 kWh			
TL5 Essential 28W/830 1SL/40			
TL5 Essential 28W/830 1SL/40			
871150057043755			
927926783058			
92/926/83058			
927926783058			

### TL5 Essential HE Super 80


Numerator - Packs per outer box	40	
EAN/UPC - Case	8711500570444	

#### Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL5 Essential 28W/830	17.0 mm	1,149.0 mm	1,156.1 mm	1,153.7 mm	1,163.2 mm
1SL/40					

#### Photometric data



Spectral Power Distribution Colour - TL5 Essential 28W/830 1SL/40



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.