



MASTER TL5 High Efficiency

MASTER TL5 HE 35W/865 SLV/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G5 na [Not Applicable]			
Features				
Flux measurement reference	Sphere			
Light Technical				
Color Code	865 [CCT of 6500K]			
Luminous Flux	3,100 lm			
Color Designation	Cool Daylight			
Chromaticity Coordinate X (Nom)	0.313			
Chromaticity Coordinate Y (Nom)	0.337			
Correlated Color Temperature (Nom)	6500 K			
Luminous Efficacy (rated) (Nom)	87 lm/W			
Color rendering index (CRI)	82			

Operating and Electrical	
Power Consumption	34.9 W
Lamp Current (Nom)	0.175 A
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	T5
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Nom)	1.2 mg
Energy Consumption kWh/1000 h	35 kWh
EPREL Registration Number	423544


Datasheet, 2023, April 14 data subject to change

MASTER TL5 High Efficiency

Product Data	
Order product name	MASTER TL5 HE 35W/865 SLV/40
Full product name	MASTER TL5 HE 35W/865 SLV/40
Full product code	871150071018555
Order code	927927086555
Material Nr. (12NC)	927927086555


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500710185
Numerator - Packs per outer box	40
EAN/UPC - Case	8711500867698

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE 35W/865	17 mm	1,449.0 mm	1,456.1 mm	1,453.7 mm	1,463.2 mm
SLV/40					


Photometric data



Spectral Power Distribution Colour - MASTER TL5 HE 35W/865 SLV/40

Lifetime






Life Expectancy Diagram - MASTER TL5 HE 35W/865 SLV/40

Life Expectancy Diagram - MASTER TL5 HE 35W/865 SLV/40

MASTER TL5 High Efficiency

Lifetime



Lumen Maintenance Diagram - MASTER TL5 HE 35W/865 SLV/40

