



MASTER TL5 High Output



MASTER TL5 HO 49W/840 UNP/40

This TL5 lamp (tube diameter 16 mm) offers high light output. The TL5 HO lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


| General Information | | Operating and Electrical | |
|------------------------------------|---------------------|-------------------------------|---------|
| Cap-Base | G5 | Power Consumption | 49.3 W |
| Features | na [Not Applicable] | Lamp Current (Nom) | 0.255 A |
| Flux measurement reference | Sphere | | |
| Light Technical | | Controls and Dimming | |
| Color Code | 840 [CCT of 4000K] | Dimmable | Yes |
| Luminous Flux | 4,375 lm | | |
| Color Designation | Cool White (CW) | Mechanical and Housing | |
| Chromaticity Coordinate X (Nom) | 0.38 | Bulb Shape | T5 |
| Chromaticity Coordinate Y (Nom) | 0.38 | | |
| Correlated Color Temperature (Nom) | 4000 K | Approval and Application | |
| Luminous Efficacy (rated) (Nom) | 89 lm/W | Energy Efficiency Class | G |
| Color rendering index (CRI) | 80 | Mercury (Hg) Content (Nom) | 1.2 mg |
| | | Energy Consumption kWh/1000 h | 50 kWh |
| | | EPREL Registration Number | 423547 |

MASTER TL5 High Output

| Product Data | |
|---------------------|------------------------------|
| Order product name | MASTER TL5 HO 49W/840 UNP/40 |
| Full product name | MASTER TL5 HO 49W/840 UNP/40 |
| Full product code | 871150063758155 |
| Order code | 927927584018 |
| Material Nr. (12NC) | 927927584018 |


| | |
|---------------------------------|---------------|
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8711500637581 |
| Numerator - Packs per outer box | 40 |
| EAN/UPC - Case | 8711500637598 |

Dimensional drawing




| Product | D (max) | A (max) | B (max) | B (min) | C (max) |
|------------------------------|---------|------------|------------|------------|------------|
| MASTER TL5 HO 49W/840 UNP/40 | 17 mm | 1,449.0 mm | 1,456.1 mm | 1,453.7 mm | 1,463.2 mm |

Photometric data




Spectral Power Distribution Colour - MASTER TL5 HO 49W/840 UNP/40

Lifetime



Life Expectancy Diagram - MASTER TL5 HO 49W/840 UNP/40



Lumen Maintenance Diagram - MASTER TL5 HO 49W/840 UNP/40

MASTER TL5 High Output

Lifetime

Life Expectancy Diagram - MASTER TL5 HO 49W/840 UNP/40

