

Lighting

PHILIPS

MASTER TL5 High Output

MASTER TL5 HO 24W/830 1SL/40

This TL5 lamp (tube diameter 16 mm) offers high light output. The TL5 HO lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General Information | | Operating and Electrical | |
|------------------------------------|---------------------|-------------------------------|-----------------|
| Cap-Base | G5 [G5] | Power Consumption | 22.7 W |
| Features | na [Not Applicable] | Lamp Current (Nom) | 0.295 A |
| Flux measurement reference | Sphere | | |
| | | Controls and Dimming | |
| Light Technical | | Dimmable | Yes |
| Color Code | 830 [CCT of 3000K] | | |
| Luminous Flux | 1,700 lm | Mechanical and Housing | |
| Color Designation | Warm White (WW) | Bulb Shape | T5 [16 mm (T5)] |
| Chromaticity Coordinate X (Nom) | 0.44 | | |
| Chromaticity Coordinate Y (Nom) | 0.403 | Approval and Application | |
| Correlated Color Temperature (Nom) | 3000 K | Energy Efficiency Class | G |
| Luminous Efficacy (rated) (Nom) | 76 lm/W | Mercury (Hg) Content (Nom) | 1.2 mg |
| Color rendering index (CRI) | 82 | Energy Consumption kWh/1000 h | 23 kWh |
| | | EPREL Registration Number | 423553 |


MASTER TL5 High Output

| Product Data | | | |
|---------------------|------------------------------|--|--|
| Order product name | MASTER TL5 HO 24W/830 SLV/40 | | |
| Full product name | MASTER TL5 HO 24W/830 1SL/40 | | |
| Full product code | 871150063958555 | | |
| Order code | 63958555 | | |
| Material Nr. (12NC) | 927928083055 | | |


| Numerator - Quantity Per Pack | 1 | | |
|---------------------------------|---------------|--|--|
| | 8711500639585 | | |
| EAN/UPC - Product/Case | | | |
| Numerator - Packs per outer box | 40 | | |
| EAN/UPC - Case | 8711500867759 | | |
| | | | |

Dimensional drawing

| Product | D (max) | A (max) | B (max) | B (min) | C (max) |
|-----------------------|---------|----------|----------|----------|----------|
| MASTER TL5 HO 24W/830 | 17 mm | 549.0 mm | 556.1 mm | 553.7 mm | 563.2 mm |
| SLV/40 | | | | | |




Photometric data




Spectral Power Distribution Colour - MASTER TL5 HO 24W/830 SLV/40

Lifetime








Life Expectancy Diagram - MASTER TL5 HO 24W/830 SLV/40

MASTER TL5 High Output

Lifetime



Lumen Maintenance Diagram - MASTER TL5 HO 24W/830 SLV/40



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 16 - data subject to change