MASTER TL5 High Output

MASTER TL5 HO 24W/865 1SL/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information					
Cap base	G5 [G5] na [Not Applicable]				
Features					
Flux measurement reference	Sphere				
Light Technical					
Colour Code	865 [CCT of 6500K]				
Luminous Flux	1,575 lm				
Colour designation	Cool Daylight				
Chromaticity Coordinate X (Nom)	0.313				
Chromaticity Coordinate Y (Nom)	0.337				
Correlated Colour Temperature	6500 K				
Luminous efficacy (rated) (nom.)	72 lm/W				
Colour rendering index (CRI)	82				
Operating and Electrical					
Power Consumption	22.7 W				
Lamp current (nom.)	0.295 A				

Controls and Dimming			
Dimmable	Yes		
Mechanical and Housing			
Bulb shape	T5 [16 mm (T5)]		
Approval and Application			
Energy Efficiency Class	G		
Mercury (Hg) content (nom.)	1.2 mg		
Energy consumption kWh/1,000 hours	23 kWh		
EPREL registration number	423556		
Product Data			
Order product name	MASTER TL5 HO 24W/865 SLV/40		
Full product name	MASTER TL5 HO 24W/865 1SL/40		
Full EOC	871150064393355		
Order code	64393355		
Material no. (12 NC)	927928086555		
SAP numerator - quantity per pack	1		






PHILIPS

Lighting

MASTER TL5 High Output


EAN/UPC — Product/Case	8711500643933
Numerator – packs per outer box	40
EAN/UPC - Case	8711500867858

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO 24W/865	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm
SLV/40					

Photometric data




Spectral Power Distribution Colour - MASTER TL5 HO 24W/865 SLV/40

Lifetime








Life Expectancy Diagram - MASTER TL5 HO 24W/865 SLV/40

MASTER TL5 High Output

Lifetime



Lumen Maintenance Diagram - MASTER TL5 HO 24W/865 SLV/40



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 14 - data subject to change