



MASTER TL5 High Output Xtra

MASTER TL5 HO Xtra 80W/830 SLV/20

This TL5 lamp (tube diameter 16 mm) combines the advantages of a TL5 High Output lamp (TL5 HO lamps are optimized for installations requiring high light output and offer excellent lumen maintenance and color rendering) with a long and reliable lifetime. This results in extra-low maintenance costs and saves on expensive spot replacement. Main applications are places where lamp replacement costs and/or costs of disruption are high.

Warnings and Safety

- · Philips HF Xtreme gear ensures longest lifetime.
- · To achieve lifetimes as published for 100% operation, dimming below 30% should not be applied.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G5 [G5]			
Light Technical				
Color Code	830 [CCT of 3000K]			
Luminous Flux	7,000 lm			
Color Designation	Warm White (WW)			
Correlated Color Temperature (Nom)	3000 K			
Luminous Efficacy (rated) (Nom)	80 lm/W			
Color rendering index (CRI)	82			

Operating and Electrical			
Power Consumption	79.8 W		
Lamp Current (Nom)	0.530 A		
Controls and Dimming			
Dimmable	Yes		
Mechanical and Housing			
Bulb Shape	T5 [16 mm (T5)]		
Approval and Application			
Mercury (Hg) Content (Nom)	3.0 mg		


Datasheet, 2023, September 21 data subject to change

MASTER TL5 High Output Xtra

Energy Consumption kWh/1000 h	88 kWh			
Product Data				
Order product name	MASTER TL5 HO Xtra 80W/830 SLV/20			
Full product name	MASTER TL5 HO Xtra 80W/830 SLV/20			
Full product code	871150026261505			
Order code	927929783026			


Material Nr. (12NC)	927929783026
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500262615
Numerator - Packs per outer box	20
EAN/UPC - Case	8711500262882

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO Xtra	17 mm	1,449.0 mm	1,456.1 mm	1,453.7 mm	1,463.2 mm
80W/830 SLV/20					


Photometric data



Spectral Power Distribution Colour - MASTER TL5 HO Xtra 80W/830 SLV/20

Lifetime






Life Expectancy Diagram - MASTER TL5 HO Xtra 80W/830 SLV/20

Life Expectancy Diagram - MASTER TL5 HO Xtra 80W/830 SLV/20

MASTER TL5 High Output Xtra

Lifetime





Life Expectancy Diagram - MASTER TL5 HO Xtra 80W/830 SLV/20

Lumen Maintenance Diagram - MASTER TL5 HO Xtra 80W/830 SLV/20

