



MASTER TL5 High Output Xtra

MASTER TL5 HO Xtra 80W/840 1SL/20

This TL5 lamp (tube diameter 16 mm) combines the advantages of a TL5 High Output lamp (TL5 HO lamps are optimized for installations requiring high light output and offer excellent lumen maintenance and color rendering) with a long and reliable lifetime. This results in extra-low maintenance costs and saves on expensive spot replacement. Main applications are places where lamp replacement costs and/or costs of disruption are high.

Warnings and Safety

- · Philips HF Xtreme gear ensures longest lifetime.
- · To achieve lifetimes as published for 100% operation, dimming below 30% should not be applied.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G5 [G5]			
Flux measurement reference	Sphere			
Light Technical				
Color Code	840 [CCT of 4000K]			
Luminous Flux	6,400 lm			
Color Designation	Cool White (CW)			
Chromaticity Coordinate X (Nom)	0.38			
Chromaticity Coordinate Y (Nom)	0.38			
Correlated Color Temperature (Nom)	4000 K			
Luminous Efficacy (rated) (Nom)	80 lm/W			

Color rendering index (CRI)	80			
Operating and Electrical				
Power Consumption	80.4 W			
Lamp Current (Nom)	0.530 A			
Controls and Dimming				
Dimmable	Yes			
Mechanical and Housing				
Bulb Shape	T5 [16 mm (T5)]			

Datasheet, 2023, April 16 data subject to change

MASTER TL5 High Output Xtra

G
3 mg
3.0 mg
81 kWh
423574

MASTER TL5 HO Xtra 80W/840 SLV/20


MASTER TL5 HO Xtra 80W/840 1SL/20

Full product code	871150026303205			
Order code	26303205			
Material Nr. (12NC)	927929784026			
Numerator - Quantity Per Pack	1			
EAN/UPC - Product/Case	8711500263032			
Numerator - Packs per outer box	20			
EAN/UPC - Case	8711500263049			

Dimensional drawing


Order product name

Full product name



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO Xtra	17 mm	1,449.0 mm	1,456.1 mm	1,453.7 mm	1,463.2 mm
80W/840 SLV/20					


Photometric data




Spectral Power Distribution Colour - MASTER TL5 HO Xtra 80W/840 SLV/20


MASTER TL5 High Output Xtra

Lifetime





Life Expectancy Diagram - MASTER TL5 HO Xtra 80W/840 SLV/20



Life Expectancy Diagram - MASTER TL5 HO Xtra 80W/840 SLV/20



Life Expectancy Diagram - MASTER TL5 HO Xtra 80W/840 SLV/20

Lumen Maintenance Diagram - MASTER TL5 HO Xtra 80W/840 SLV/20



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.