PHILIPS Lighting



MASTER PL-S 4 Pin



MASTER PL-S 11W/827/4P 1CT/5X10BOX

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 2 parallel narrow fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- · Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Lamp current (nom.)	0.160 A		
Cap base	2G7				
Flux measurement reference	Sphere	Controls and Dimming	Controls and Dimming		
		Dimmable	Yes		
Light Technical					
Colour Code	827 [CCT of 2700K]	Approval and Application			
Luminous Flux	900 lm	Energy Efficiency Class	G		
Colour designation	Incandescent White	Mercury (Hg) content (max.)	1.4 mg		
Chromaticity Coordinate X (Nom)	0.463	Mercury (Hg) content (nom.)	1.4 mg		
Chromaticity Coordinate Y (Nom)	0.42	Energy consumption kWh/1,000 hours	12 kWh		
Correlated Colour Temperature	2700 K	EPREL registration number	423599		
Luminous efficacy (rated) (nom.)	80 lm/W				
Colour rendering index (CRI)	82	Product Data			
		Order product name	MASTER PL-S 11W/827/4P 1CT/5X10BOX		
Operating and Electrical		Full product name	MASTER PL-S 11W/827/4P 1CT/5X10BOX		
Power Consumption	11.9 W	Full EOC	871150026114470		
		Order code	26114470		

MASTER PL-S 4 Pin

Material no. (12 NC)	927936682711		
Local order code	11PLS8274PINB		
SAP numerator - quantity per pack	1		
EAN/UPC — Product/Case	8711500261144		


Numerator – packs per outer box	50
EAN/UPC - Case	8711500261168

Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-S 11W/827/4P 1CT/	28 mm	13 mm	196 mm	214 mm	219.9 mm
5X10BOX					

Photometric data




Spectral Power Distribution Colour - MASTER PL-S 11W/827/4P 1CT/5X10BOX

Lifetime




Life Expectancy Diagram - MASTER PL-S 11W/827/4P 1CT/5X10BOX



Life Expectancy Diagram - MASTER PL-S 11W/827/4P 1CT/5X10BOX

MASTER PL-S 4 Pin

Lifetime



Lumen Maintenance Diagram - MASTER PL-S 11W/827/4P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 14 - data subject to change