



# **MASTER PL-S 4 Pin**

# MASTER PL-S 11W/830/4P 1CT/5X10BOX

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

#### **Warnings and Safety**

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- · Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information				
Cap-Base	2G7 [2G7]			
Flux measurement reference	Sphere			
Light Technical				
Color Code	830 [CCT of 3000K]			
Luminous Flux	900 lm			
Color Designation	Warm White (WW)			
Chromaticity Coordinate X (Nom)	0.44			
Chromaticity Coordinate Y (Nom)	0.403			
Correlated Color Temperature (Nom)	3000 K			
Luminous Efficacy (rated) (Nom)	82 lm/W			
Color rendering index (CRI)	82			

Operating and Electrical	
Power Consumption	11.9 W
Lamp Current (Nom)	0.160 A
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	1.4 mg
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	12 kWh
EPREL Registration Number	423600


Datasheet, 2023, April 16 data subject to change

## **MASTER PL-S 4 Pin**

Product Data	
Order product name	MASTER PL-S 11W/830/4P 1CT/5X10BOX
Full product name	MASTER PL-S 11W/830/4P 1CT/5X10BOX
Full product code	871150026119970
Order code	26119970
Material Nr. (12NC)	927936683011


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500261199
Numerator - Packs per outer box	50
EAN/UPC - Case	8711500261212

## Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-S 11W/830/4P 1CT/	28 mm	13 mm	196 mm	214 mm	219.9 mm
5X10BOX					


## Photometric data



Spectral Power Distribution Colour - MASTER PL-S 11W/830/4P 1CT/5X10BOX

## Lifetime





Life Expectancy Diagram - MASTER PL-S 11W/830/4P 1CT/5X10BOX

Life Expectancy Diagram - MASTER PL-S 11W/830/4P 1CT/5X10BOX

## **MASTER PL-S 4 Pin**

## Lifetime



Lumen Maintenance Diagram - MASTER PL-S 11W/830/4P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.