



MASTER TL5 Circular

MASTER TL5 Circular 40W/865 1CT/10

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omnidirectional light distribution. It is suitable for a wide range of professional and semi-professional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	2GX13 [2GX13]
Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux	3,100 lm
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	78 lm/W
Color rendering index (CRI)	82
Operating and Electrical	
Power Consumption	39.9 W
Lamp Current (Nom)	0.320 A


Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	C-T5 [C-T5 16 mm]
Approval and Application	
Mercury (Hg) Content (Nom)	2.5 mg
Product Data	
Order product name	MASTER TL5 Circular 40W/865 1CT/10
Full product name	MASTER TL5 Circular 40W/865 1CT/10
Full product code	871150027650600
Order code	927965586513
Material Nr. (12NC)	927965586513
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500276506
· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·

Datasheet, 2023, April 29 data subject to change

MASTER TL5 Circular

Numerator - Packs per outer box	10
EAN/UPC - Case	8711500276469

Dimensional drawing




 Product
 D (max)
 D (min)
 E (min)
 E (max)
 I (min)
 I (max)

 MASTER TL5 Circular 40W/865
 18 mm
 14 mm
 293 mm
 305 mm
 260 mm
 272 mm


 1CT/10
 10 mm
 10 mm


Photometric data



Spectral Power Distribution Colour - MASTER TL5 Circular 40W/8651CT/10

Lifetime






Life Expectancy Diagram - MASTER TL5 Circular 40W/865 1CT/10

Life Expectancy Diagram - MASTER TL5 Circular 40W/865 1CT/10

MASTER TL5 Circular

Lifetime



Lumen Maintenance Diagram - MASTER TL5 Circular 40W/865 1CT/10



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.