PHILIPS Lighting



MASTER TL5 Circular

TL5C 55W/840 1CT/10

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omnidirectional light distribution. It is suitable for a wide range of professional and semiprofessional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Lamp Current (Nom)	0.550 A		
Cap-Base	2GX13 [2GX13]				
Nominal lifetime	12,000 hour(s)	Controls and Dimming			
Flux measurement reference	Sphere	Dimmable	Yes		
Light Technical		Mechanical and Housing			
Color Code	841 [CCT of 4100K]	Bulb Shape	C-T5 [C-T5 16 mm]		
Luminous Flux	4,210 lm				
Color Designation	Cool White (CW)	Approval and Application			
Chromaticity Coordinate X (Nom)	0.38	Energy Efficiency Class	G		
Chromaticity Coordinate Y (Nom)	0.38	Mercury (Hg) Content (Max)	4 mg		
Correlated Color Temperature (Nom)	4000 K	Mercury (Hg) Content (Nom)	4 mg		
Luminous Efficacy (rated) (Nom)	76 lm/W	Energy Consumption kWh/1000 h	56 kWh		
Color rendering index (CRI)	81	EPREL Registration Number	423623		
Operating and Electrical		Product Data			
Power Consumption	55.7 W	Order product name	MASTER TL5 Circular 55W/840 1CT/10		

MASTER TL5 Circular

Full product name	TL5C 55W/840 1CT/10			
Full product code	871150064251625			
Order code	165928			
Material Nr. (12NC)	927965784013			
Numerator - Quantity Per Pack	1			


EAN/UPC - Product/Case	8711500642516			
Numerator - Packs per outer box	10			
EAN/UPC - Case	8711500642523			

Dimensional drawing




Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
MASTER TL5 Circular 55W/840	18 mm	14 mm	293 mm	305 mm	260 mm	272 mm
1CT/10						

Photometric data




Spectral Power Distribution Colour - MASTER TL5 Circular 55W/840 1CT/10

Lifetime




Life Expectancy Diagram - MASTER TL5 Circular 55W/840 1CT/10



Life Expectancy Diagram - MASTER TL5 Circular 55W/840 1CT/10

MASTER TL5 Circular

Lifetime



Lumen Maintenance Diagram - MASTER TL5 Circular 55W/840 1CT/10



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 24 - data subject to change