



MASTER TL-D Xtreme



MASTER TL-D Xtreme 58W/830 SLV

This MASTER TL-D Xtreme lamp offers extremely long lifetime. This results in extra-low lamp cost over life. It is therefore suitable for places where lamp replacement is expensive, due to high ceilings or disturbance of operations, and applications with long burning cycles, e.g. tunnels, oil rigs, manufacturing lines. It can be operated on existing gear or dedicated HF Xtreme gear.

Warnings and Safety

- To achieve published lifetimes for 100% operation, do not dim below 30%
- When used on electromagnetic gear, it is strongly recommended to apply only Philips S10 or S10E starters (for 18W types S2 or S2E) to achieve the published lifetimes, and to install new starters when relamping.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	47,000 hour(s)
Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	5,100 lm
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.44
Chromaticity Coordinate Y (Nom)	0.403
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	88 lm/W

Color rendering index (CRI)	82
Operating and Electrical	
Power Consumption	58.9 W
Lamp Current (Nom)	0.665 A
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	T8
Approval and Application	
Energy Efficiency Class	G

MASTER TL-D Xtreme


Mercury (Hg) Content (Max)	3 mg
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	59 kWh
EPREL Registration Number	423632

Product Data

Order product name	MASTER TL-D Xtreme 58W/830 SLV
Full product name	MASTER TL-D Xtreme 58W/830 SLV
Full product code	871150055882440


Order code	927983383014
Material Nr. (12NC)	927983383014
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500558824
Numerator - Packs per outer box	25
EAN/UPC - Case	8711500558855

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Xtreme 58W/830 SLV	28 mm	1,500.0 mm	1,507.1 mm	1,504.7 mm	1,514.2 mm



Photometric data



Spectral Power Distribution Colour - MASTER TL-D Xtreme 58W/830 SLV



MASTER TL-D Xtreme

Lifetime



Life Expectancy Diagram - MASTER TL-D Xtreme 58W/830 SLV

Life Expectancy Diagram - MASTER TL-D Xtreme 58W/830 SLV



Life Expectancy Diagram - MASTER TL-D Xtreme 58W/830 SLV

Lumen Maintenance Diagram - MASTER TL-D Xtreme 58W/830 SLV

