PHILIPS

Lighting



T5 High Output

F39T5/830/HO/ALTO 40PK

Philips T5 HO lamps are environmentally-responsible, ultra-slim and have extraordinary light output and longer life.

Product data

General Information	
Cap-Base	G5
Features	HO Alto® [High Output Alto]

Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	3,500 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	82 lm/W
Color rendering index (CRI)	82

Operating and Electrical	
Power Consumption	38.0 W
Lamp Current (Nom)	0.325 A

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Shape	T5

Approval and Application	
Mercury (Hg) Content (Nom)	1.4 mg

Product Data	
Order product name	39W/830 Min Bipin T5 HO ALTO UNP
Full product name	F39T5/830/HO/ALTO 40PK
Order code	290221
Material Nr. (12NC)	927992683022
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677290221
Numerator - Packs per outer box	40
EAN/UPC - Case	50046677290226


T5 High Output

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
39W/830 Min Bipin T5 HO ALTO UNP	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm

Photometric data




Spectral Power Distribution Colour - 39W/830 Min Bipin T5 HO ALTO UNP

Lifetime



Life Expectancy Diagram - 39W/830 Min Bipin T5 HO ALTO UNP



Lumen Maintenance Diagram - 39W/830 Min Bipin T5 HO ALTO UNP

T5 High Output

Lifetime

Life Expectancy Diagram - 39W/830 Min Bipin T5 HO ALTO UNP

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.