



UVA TL

TL-K 40W UV-A 1SL/25

Philips offers highly quality TL lamps emitting UV-A in a spectral distribution wavelength of between 315 to 380 nm. This makes these lamps suitable for various applications such as phototherapy, curing & Photocatalytic oxidation

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take them to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Photobiological safety – IEC 62471 – Risk Group 2. CAUTION – UV Emitted from these products.


Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% Failures (Nom)	1,000 hour(s)
Useful Life (Nom)	1,000 hour(s)
Light Technical	
Color Code	209
Color Designation	Ultra Violet A
Chromaticity Coordinate X (Nom)	226
Chromaticity Coordinate Y (Nom)	220
Operating and Electrical	
Power Consumption	40.5 W
Lamp Current (Nom)	0.86 A
Voltage (Nom)	50 V
Voltage (Nom)	50 V
Mechanical and Housing	
Bulb Shape	T38 [T 38mm]

UV	
UV-A Radiation 0Hr (IEC)	7.9 W
UV-A Radiation 100Hr (IEC)	7.7 W
Product Data	
Full product code	871150062830540
Order product name	TL-K 40W UV-A 1SL/25
Order code	928003120912
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	928003120912
Full product name	TL-K 40W UV-A 1SL/25
EAN/UPC - Case	8711500628404
EAN/UPC - Product/Case	8711500628305

UVA TL

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-K 40W UV-A 1SL/25	40.5 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

