



TL-D Standard Colours

TL-D 10W/33-640 1SL/25

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% Failures (Nom)	5,000 hour(s)
Light Technical	
Color Code	33-640
Luminous Flux	440 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4100 K
Color rendering index (CRI)	60
Operating and Electrical	
Power Consumption	10 W
Lamp Current (Nom)	0.230 A
Voltage (Nom)	46 V
Voltage (Nom)	46 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	T8
Approval and Application	
Mercury (Hg) Content (Nom)	8.0 mg
Product Data	
Order product name	TL-D 10W/33-640 1SL/25
Full product name	TL-D 10W/33-640 1SL/25
Full product code	871150064128100
Order code	928024003331
Material Nr. (12NC)	928024003331
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500641281
Numerator - Packs per outer box	25
EAN/UPC - Case	8711500641298


TL-D Standard Colours

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 10W/33-640 1SL/25	28 mm	331.5 mm	338.6 mm	336.2 mm	345.7 mm

Photometric data




Spectral Power Distribution Colour - TL-D 10W/33-640 1SL/25

Lifetime



Life Expectancy Diagram - TL-D 10W/33-640 1SL/25



Life Expectancy Diagram - TL-D 10W/33-640 1SL/25

TL-D Standard Colours

Lifetime



Lumen Maintenance Diagram - TL-D 10W/33-640 1SL/25

