

TL-E LIFEMAX Standard Colours

TL-E 40W/54-765 1CT/20

This circular TL lamp (tube diameter 29 mm) enables omni-directional light distribution. It is suitable for use in a wide range of luminaires for various purposes where color rendering is not important.

Product data

General Information	
Cap-Base	G10q
Nominal lifetime	8,000 hour(s)
Life to 50% Failures (Nom)	13,000 hour(s)

Light Technical	
Color Code	54-765
Luminous Flux	2,500 lm
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6200 K
Luminous Efficacy (rated) (Nom)	62 lm/W
Color rendering index (CRI)	72

Operating and Electrical	
Power Consumption	40.0 W
Lamp Current (Nom)	0.420 A
Voltage (Nom)	110 V
Voltage (Nom)	110 V

Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Shape	C-T29

Approval and Application	
Mercury (Hg) Content (Nom)	9 mg

Product Data	
Order product name	TL-E 40W/54-765 1CT/20
Full product name	TL-E 40W/54-765 1CT/20
Full product code	871150055991301
Order code	928027405436
Material Nr. (12NC)	928027405436
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500559913
Numerator - Packs per outer box	20
EAN/UPC - Case	8711500284501


TL-E LIFEMAX Standard Colours

Dimensional drawing



Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
TL-E 40W/54-765 1CT/20	30.9 mm	27.1 mm	393.7 mm	406.4 mm	341.0 mm	347.7 mm

Photometric data



Spectral Power Distribution Colour - TL-E 40W/54-765 1CT/20

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.