

MASTERColour CDM-R Elite

MASTERColour CDM-R Elite 35W/942 E27 PAR30L 30D

Compact, very high-efficiency, long-life Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high colour rendering

Warnings and Safety

- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)

Product data

General Information	
Cap base	E27 [E27]
Operating position	UNIVERSAL [Any or Universal (U)]
Switching Cycle	1,350
Life to 50% failures (nom.)	15,000 h

Light Technical	
Colour Code	942 [CCT of 4200K]
Beam angle (nom.)	30 degree(s)
Luminous intensity (nom.)	7,800 cd
Colour designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	0.373
Chromaticity Coordinate Y (Nom)	0.369
Correlated Colour Temperature	4200 K
Luminous efficacy (rated) (nom.)	68 lm/W
Colour rendering index (CRI)	90
LLMF at end of nominal lifetime (nom.)	70 %
Luminous flux in 90° cone (rated)	2,350 lm

Operating and Electrical	
Power Consumption	39.0 W
Warm-up time to 60% light	120 s
Voltage (nom.)	92 V
Voltage (nom.)	92 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Lamp Finish	Clear
Bulb shape	PAR30L [PAR 3.75 inch/95 mm long]

Approval and Application	
Mercury (Hg) content (nom.)	4.7 mg


MASTERColour CDM-R Elite

Energy consumption kWh/1,000 hours	43 kWh

Product Data	
Order product name	MC CDM-R Elite 35W/942 E27 PAR30L 30D
Full product name	MASTERColour CDM-R Elite 35W/942 E27 PAR30L 30D
Full EOC	871829165153600
Order code	65153600


Material no. (12 NC)	928051100630
Local order code	35CDMRELP394230
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8718291651536
Numerator – packs per outer box	6
EAN/UPC - Case	8718291651543


Dimensional drawing



Product	D (max)	C (max)
MC CDM-R Elite 35W/942 E27 PAR30L 30D	97 mm	123 mm

Photometric data






Light Distribution Diagram - MC CDM-R Elite 35W/942 E27 PAR30L 30D


Spectral Power Distribution Colour - MC CDM-R Elite 35W/942 E27 PAR30L 30D

MASTERColour CDM-R Elite

Lifetime



Life Expectancy Diagram - MC CDM-R Elite 35W/942 E27 PAR30L 30D



Lumen Maintenance Diagram - MC CDM-R Elite 35W/942 E27 PAR30L 30D

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.