

HPL-N

HPL-N 400W/542 E40 HG 1SL/6

标准高压汞灯

安全提示

- For use with control gear designed for high-pressure mercury lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般信息	
底盖	E40 [E40]
操作位置	UNIVERSAL [任意或通用 (U)]
50% 故障条件下的使用寿命 (标称)	16,000 小时

灯技术	
颜色代码	542 [CCT of 4200K]
颜色名称	冷白色 (CW)
色度坐标 X (标称)	384
色度坐标 Y (标称)	384
相关色温 (标称)	4200 K
光效 (额定)(标称)	55 lm/W
显色指数 (CRI)	50

操作和电气	
功耗	400.0 W
电压 (标称)	140 V
电压 (标称)	140 V

控制和调光	
可调光	否

机械和外壳	
灯泡外观	镀膜玻璃
灯泡材料	硬玻璃
灯泡外形	ED120 [ED 120 毫米]


审批和申请	
汞 (Hg) 含量 (标称)	72 mg
能耗 kWh/1000 h	440 kWh

产品数据	
订单产品名称	HPL-N 400W/542 E40 HG 1SL/6
完整的产品名称	HPL-N 400W/542 E40 HG 1SL/6
完整产品代码	871150018045299
订购代码	928053507496
材料编号 (12NC)	928053507496
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8711500180452

HPL-N


计算器 - 每个外包装箱中的包数	6
EAN/UPC - 案例	8711500200150

二维绘图




Product	D (max)	C (max)
HPL-N 400W/542 E40 HG 1SL/6	122 mm	290 mm

光度数据




Spectral Power Distribution Colour - HPL-N 400W/542 E40 HG 1SL/6

寿命



Life Expectancy Diagram - HPL-N 400W/542 E40 HG 1SL/6



Lumen Maintenance Diagram - HPL-N 400W/542 E40 HG 1SL/6

© 2023 Signify Holding 保留所有权利。 Signify 对此文档所包含信息的准确性或完整性不作任何陈述或保证，也不对根据此文档信息做出的任何行为负责。 本文档中提供的信息不作为任何商业要约，也不构成任何报价或合同的一部分，除非 Signify 同意。 Philips 和 Philips Shield Emblem 是 Koninklijke Philips N.V. 的注册商标。

www.lighting.philips.com
2023, 四月 16 - 要更改的数据主题