



MASTERColour CDM-T Evolution

MASTERColour CDM-T Evolution 20W/930 G12

Single-ended, highest-efficiency, longest-life Ceramic Metal Halide discharge lamp producing crisp white sparkling light with high colour rendering

Warnings and Safety

- Use only in a totally enclosed luminaire, even during testing (IEC61167, IEC62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- The vast majority of drivers are fully compatible with CDM Evolution lamps. However, best performance is guaranteed with Philips drivers.
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- CDM Evolution lamps are designed to comply with IEC standards
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	G12 [G12]
Operating position	UNIVERSAL [Any or Universal (U)]
Life to 50% failures (nom.)	25,000 h

Light Technical	
Colour Code	930 [CCT of 3000K]
Colour designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.43
Chromaticity Coordinate Y (Nom)	0.393
Correlated Colour Temperature	3000 K


Luminous efficacy (rated) (nom.)	102 lm/W
Colour rendering index (CRI)	90
Arc Length O (Nom)	3.6 mm

Operating and Electrical	
Power Consumption	20.0 W
Voltage (nom.)	105 V
Voltage (nom.)	105 V


MASTERColour CDM-T Evolution

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Lamp Finish	Clear
Bulb shape	T19 [T 19 mm]
Approval and Application	
Mercury (Hg) content (nom.)	3.0 mg
Energy consumption kWh/1,000 hours	22 kWh
Product Data	
Order product name	MC CDM-T Evolution 20W/930 G12

Dimensional drawing




Photometric data



Light Distribution Diagram - MC CDM-T Evolution 20W/930 G12

Full product name	MASTERColour CDM-T Evolution 20W/930 G12
Full EOC	871829165912900
Order code	65912900
Material no. (12 NC)	928064705131
Local order code	20CDMTEVO930
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718291659129
Numerator – packs per outer box	12
EAN/UPC – Case	8718291659136


Product	D (max)	O	L (min)	L (max)	L	C (max)
MC CDM-T Evolution 20W/930 G12	20 mm	3.6 mm	55 mm	57 mm	56 mm	103 mm




Spectral Power Distribution Colour - MC CDM-T Evolution 20W/930 G12

MASTERColour CDM-T Evolution

Lifetime



Lumen Maintenance Diagram - MC CDM-T Evolution 20W/930 G12



Life Expectancy Diagram - MC CDM-T Evolution 20W/930 G12

