PHILIPS Lighting



MASTERColour CDM-R

MASTERC CDM-R 70W/830 E27 PAR30L 10D 1CT

Range of compact, high-efficiency, discharge reflector lamps with a stable colour over lifetime and a crisp, sparkling light

Warnings and Safety

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. Color 830 lamps may also use electromagnetic gear.
- Use only with electronic control gear. Colour 830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


eneral Information		Color rendering index (CRI)	81
ap-Base	E27 [E27]	LLMF At End Of Nominal Lifetime (No	om) 62 %
Operating Position	UNIVERSAL [Any or Universal (U)]	Luminous Flux in 90° Cone (Rated)	4,250 lm
Switching Cycle	1,050		
Life to 50% Failures (Nom)	12,000 hour(s)	Operating and Electrical	
		Power Consumption	73.2 W
Light Technical		Warm-up time to 60% light	120 s
Color Code	830 [CCT of 3000K]	Voltage (Nom)	90 V
Beam Angle (Nom)	10 degree(s)	Voltage (Nom)	90 V
Luminous Intensity (Nom)	68,000 cd		
Color Designation	Warm White (WW)	Controls and Dimming	
Chromaticity Coordinate X (Nom)	0.427	Dimmable	No
Chromaticity Coordinate Y (Nom)	0.397		
Correlated Color Temperature (Nom)	3000 K		

MASTERColour CDM-R


Mechanical and Housing				
Bulb Finish	Clear			
Bulb Shape	PAR30L [PAR 3.75 inch/95mm Long]			
Approval and Application				
Mercury (Hg) Content (Nom)	8.3 mg			
Energy Consumption kWh/1000 h	80 kWh			
Product Data				
Order product name	MASTERC CDM-R 70W/830 E27 PAR30L 10D			
	1CT			

Full product name	MASTERC CDM-R 70W/830 E27 PAR30L 10D			
	1CT			
Full product code	871150021172900			
Order code	928071100691			
Material Nr. (12NC)	928071100691			
Numerator - Quantity Per Pack	1			
EAN/UPC - Product/Case	8711500211729			
Numerator - Packs per outer box	6			
EAN/UPC - Case	8711500211736			

Dimensional drawing



Photometric data



Light Distribution Diagram - MASTERC CDM-R 70W/830 E27 PAR30L 10D 1CT


Product	D (max)	D	C (max)	с
MASTERC CDM-R 70W/830 E27 PAR30L 10D 1CT	97 mm	95 mm	123 mm	120 mm



Spectral Power Distribution Colour - MASTERC CDM-R 70W/830 E27 PAR30L 10D 1CT

MASTERColour CDM-R

Lifetime



Life Expectancy Diagram - MASTERC CDM-R 70W/830 E27 PAR30L 10D 1CT

⁵ 100 60 40 20 0 0 3000 6000 9000 12000 Burning hours

Lumen Maintenance Diagram - MASTERC CDM-R 70W/830 E27 PAR30L 10D 1CT



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 1 - data subject to change