



# MASTERColour CDM-T Elite

# MASTERColour CDM-T Elite 50W/942 G12 1CT

Single-ended, very high-efficiency, long-life Ceramic Metal Halide discharge lamp producing crisp white sparkling light with high color rendering

#### Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- · Use only with electronic control gear. 35W & 70W lamps may also use electromagnetic gear.
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information				
Cap-Base	G12 [G12]			
Operating Position	UNIVERSAL [Any or Universal (U)]			
Flux measurement reference	Sphere			
Life to 50% Failures (Nom)	15,000 hour(s)			
Light Technical				
Color Code	942 [CCT of 4200K]			
Luminous Flux	5,000 lm			
Color Designation	Cool White (CW)			
Chromaticity Coordinate X (Nom)	0.371			
Chromaticity Coordinate Y (Nom)	0.366			
Correlated Color Temperature (Nom)	4200 K			
Luminous Efficacy (rated) (Nom)	100 lm/W			

Color rendering index (CRI)	90
Arc Length O (Nom)	7.1 mm
Operating and Electrical	
Power Consumption	50.2 W
Voltage (Nom)	91 V
Voltage (Nom)	91 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear


Datasheet, 2023, May 15 data subject to change

# **MASTERColour CDM-T Elite**

Bulb Shape	T19 [T 19mm]
Approval and Application	
Energy Efficiency Class	F
Mercury (Hg) Content (Max)	5.7 mg
Mercury (Hg) Content (Nom)	5.7 mg
Energy Consumption kWh/1000 h	51 kWh
EPREL Registration Number	1519238
Product Data	
Order product name	MASTERC CDM-T Elite 50W/942 G12 1CT


Full product name	MASTERColour CDM-T Elite 50W/942 G12 1CT				
Full product code	871829120159500				
Order code	20159500				
Material Nr. (12NC)	928080015131				
Numerator - Quantity Per Pack	1				
EAN/UPC - Product/Case	8718291201595				
Numerator - Packs per outer box	12				
EAN/UPC - Case	8718291201601				


## Dimensional drawing




Product	D (max)	0	L (min)	L (max)	L	C (max)
MASTERC CDM-T Elite 50W/942	20 mm	7.1 mm	55 mm	57 mm	56 mm	103 mm
G12 1CT						

### Photometric data








Light Distribution Diagram - MASTERC CDM-T Elite 50W/942 G12 1CT

Spectral Power Distribution Colour - MASTERC CDM-T Elite 50W/942 G12 1CT

# **MASTERColour CDM-T Elite**

### Lifetime





Life Expectancy Diagram - MASTERC CDM-T Elite 50W/942 G12 1CT

Lumen Maintenance Diagram - MASTERC CDM-T Elite 50W/942 G12 1CT



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.