PHILIPS Lighting



MASTERColour CDM-T

MASTERColour CDM-T 150W/830 G12 1CT

Range of single-ended, compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Luminous Efficacy (rated) (Nom)	88 lm/W
Cap-Base	G12	Color rendering index (CRI)	88
Operating Position	UNIVERSAL [Any or Universal (U)]	Arc Length O (Nom)	9 mm
Flux measurement reference	Sphere		
Life to 50% Failures (Nom)	12,000 hour(s)	Operating and Electrical	
		Power Consumption	150.1 W
Light Technical		Voltage (Nom)	96 V
Color Code	830 [CCT of 3000K]	Voltage (Nom)	96 V
Luminous Flux	13,000 lm		
Color Designation	Warm White (WW)	Controls and Dimming	
Chromaticity Coordinate X (Nom)	0.434	Dimmable	No
Chromaticity Coordinate Y (Nom)	0.398		
Correlated Color Temperature (Nom)	3000 K		

MASTERColour CDM-T

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T19
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	14.3 mg
Mercury (Hg) Content (Nom)	14.3 mg
Energy Consumption kWh/1000 h	151 kWh
EPREL Registration Number	473335
Product Data	
Order product name	MASTERC CDM-T 150W/830 G12 1CT

Full product name	MASTERColour CDM-T 150W/830 G12 1CT
Full product code	871150019780115
Order code	19780115
Material Nr. (12NC)	928083705125
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500197801
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500197818


D (max) D

о


L(min) L(max) L

20 mm 0.75 inch 9 mm 55 mm 57 mm 56 mm 110 mm

Dimensional drawing



Photometric data



Product

MASTERC CDM-T

150W/830 G12 1CT


Light Distribution Diagram - MASTERC CDM-T 150W/830 G12 1CT

Spectral Power Distribution Colour - MASTERC CDM-T 150W/830 G12 1CT

C (max)

MASTERColour CDM-T

Lifetime



Life Expectancy Diagram - MASTERC CDM-T 150W/830 G12 1CT

Lumen Maintenance Diagram - MASTERC CDM-T 150W/830 G12 1CT



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 15 - data subject to change