

MASTERColour CDM-T

MASTERC CDM-T 150W/942 G12 1CT

Range of single-ended, compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G12
Operating Position	UNIVERSAL [Any or Universal (U)]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	12,000 hour(s)

Light Technical	
Color Code	942 [CCT of 4200K]
Luminous Flux	12,100 lm
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	0.371
Chromaticity Coordinate Y (Nom)	0.366
Correlated Color Temperature (Nom)	4200 K
Luminous Efficacy (rated) (Nom)	82 lm/W
Color rendering index (CRI)	96
Arc Length O (Nom)	8 mm

Operating and Electrical	
Power Consumption	150.1 W
Voltage (Nom)	90 V
Voltage (Nom)	90 V

Controls and Dimming	
Dimmable	No

MASTERColour CDM-T


Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T19

Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	10.4 mg
Mercury (Hg) Content (Nom)	10.4 mg
Energy Consumption kWh/1000 h	151 kWh
EPREL Registration Number	473338

Product Data	
Order product name	MASTERC CDM-T 150W/942 G12 1CT


Full product name	MASTERC CDM-T 150W/942 G12 1CT
Full product code	871150020005115
Order code	928084605131
Material Nr. (12NC)	928084605131
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500200051
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500200068

Dimensional drawing




Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERC CDM-T 150W/942 G12 1CT	20 mm	0.75 inch	8 mm	55 mm	57 mm	56 mm	110 mm

Photometric data




Spectral Power Distribution Colour - MASTERC CDM-T 150W/942 G12 1CT




Light Distribution Diagram - MASTERC CDM-T 150W/942 G12 1CT

MASTERColour CDM-T

Lifetime



Life Expectancy Diagram - MASTERC CDM-T 150W/942 G12 1CT



Lumen Maintenance Diagram - MASTERC CDM-T 150W/942 G12 1CT

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.