



# MASTERColour CDM-T

# **MASTERC CDM-T 150W/942 G12 1CT**

Range of single-ended, compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light

### **Warnings and Safety**

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- $\cdot$  Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### **Product data**

General Information				
Cap-Base	G12			
Operating Position	UNIVERSAL [Any or Universal (U)]			
Flux measurement reference	Sphere			
Life to 50% Failures (Nom)	12,000 hour(s)			
Light Technical				
Color Code	942 [CCT of 4200K]			
Luminous Flux	12,100 lm			
Color Designation	Cool White (CW)			
Chromaticity Coordinate X (Nom)	0.371			
Chromaticity Coordinate Y (Nom)	0.366			
Correlated Color Temperature (Nom)	4200 K			

Luminous Efficacy (rated) (Nom)	82 lm/W
Color rendering index (CRI)	96
Arc Length O (Nom)	8 mm
Operating and Electrical	
Power Consumption	150.1 W
Voltage (Nom)	90 V
Voltage (Nom)	90 V
Controls and Dimming	
Dimmable	No


Datasheet, 2023, August 2 data subject to change

# **MASTERColour CDM-T**

Mechanical and Housing					
Bulb Finish	Clear				
Bulb Shape	T19				
Approval and Application					
Energy Efficiency Class	G				
Mercury (Hg) Content (Max)	10.4 mg				
Mercury (Hg) Content (Nom)	10.4 mg				
Energy Consumption kWh/1000 h	151 kWh				
EPREL Registration Number	473338				
Product Data					
Order product name	MASTERC CDM-T 150W/942 G12 1CT				


Full product name	MASTERC CDM-T 150W/942 G12 1CT				
Full product code	871150020005115				
Order code	928084605131				
Material Nr. (12NC)	928084605131				
Local order code	CDMT150W942				
Numerator - Quantity Per Pack	1				
EAN/UPC - Product/Case	8711500200051				
Numerator - Packs per outer box	12				
EAN/UPC - Case	8711500200068				


# Dimensional drawing




Product	D (max)	D	0	L (min)	L (max)	L	C (max)
MASTERC CDM-T	20 mm	0.75 inch	8 mm	55 mm	57 mm	56 mm	110 mm
150W/942 G12 1CT							

### Photometric data









Spectral Power Distribution Colour - MASTERC CDM-T 150W/942 G12 1CT

Light Distribution Diagram - MASTERC CDM-T 150W/942 G12 1CT

# **MASTERColour CDM-T**

### Lifetime





Life Expectancy Diagram - MASTERC CDM-T 150W/942 G12 1CT

Lumen Maintenance Diagram - MASTERC CDM-T 150W/942 G12 1CT



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.