



MASTERColour CDM-TP

MASTERC CDM-TP 70W/842 PG12-2 1CT/12

防护型高效放电灯系列在整个寿命期间具有稳定的光色和明亮通透的闪光，可在开放式灯具上使用

安全提示

- Lamps may use electronic or electromagnetic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般信息	
底盖	PG12-2 [PG12-2]
操作位置	UNIVERSAL [任意或通用 (U)]
50% 故障条件下的使用寿命 (标称)	16,000 小时
灯技术	
颜色代码	842 [CCT of 4200K]
颜色名称	冷白色 (CW)
色度坐标 X (标称)	374
色度坐标 Y (标称)	378
相关色温 (标称)	4200 K
光效 (额定) (标称)	77 lm/W
显色指数 (CRI)	89
弧长 O (标称)	6 mm


操作和电气	
功耗	73.2 W
电压 (标称)	90 V
电压 (标称)	90 V
控制和调光	
可调光	否
机械和外壳	
灯泡外观	透明
灯泡外形	T31 [T 31 毫米]
审批和申请	
能效等级	G
汞 (Hg) 含量 (标称)	7.1 mg

MASTERColour CDM-TP

能耗 kWh/1000 h	81 kWh
产品数据	
订单产品名称	MASTERC CDM-TP 70W/842 PG12-2 1CT/12
完整的产品名称	MASTERC CDM-TP 70W/842 PG12-2 1CT/12
完整产品代码	871150020113315
订购代码	928085909230


材料编号 (12NC)	928085909230
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8711500201133
计算器 - 每个外包装箱中的包数	12
EAN/UPC - 案例	8711500201140

二维绘图



Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERC CDM-TP 70W/842 PG12-2 1CT/12	32.00 mm	6 mm	89 mm	93 mm	91 mm	149 mm

寿命



Lumen Maintenance Diagram - MASTERColour CDM-TP 70W/842 PG12-2 1CT/12

