



MASTERColour CDM-TC

MASTERC CDM-TC 70W/830 G8.5

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- · Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information						
Cap-Base	G8.5 [G8.5]					
Operating Position	UNIVERSAL [Any or Universal (U)]					
Life to 50% Failures (Nom)	12,000 hour(s)					
Light Technical						
Color Code	830 [CCT of 3000K]					
Color Designation	Warm White (WW)					
Chromaticity Coordinate X (Nom)	0.439					
Chromaticity Coordinate Y (Nom)	0.398					
Correlated Color Temperature (Nom)	3000 K					
Luminous Efficacy (rated) (Nom)	86 lm/W					
Color rendering index (CRI)	83					

Arc Length O (Nom)	7 mm			
Operating and Electrical				
Power Consumption	73 W			
Voltage (Nom)	83 V			
Voltage (Nom)	83 V			
Controls and Dimming				
Dimmable	No			
Mechanical and Housing				
Bulb Finish	Clear			
Bulb Material	UV-Block Quartz			


Datasheet, 2023, September 22 data subject to change

MASTERColour CDM-TC

Bulb Shape	T14 [T 14 mm]				
Approval and Application					
Mercury (Hg) Content (Nom)	4.6 mg				
Energy Consumption kWh/1000 h	80 kWh				
Product Data					
Order product name	MASTERC CDM-TC 70W/830 G8.5				
Full product name	MASTERC CDM-TC 70W/830 G8.5				


Full product code	871829118820900
Order code	928086505105
Material Nr. (12NC)	928086505105
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291188209
Numerator - Packs per outer box	12
EAN/UPC - Case	8718291188216


Dimensional drawing



Product	D (max)	D	0	L (min)	L (max)	L	C (max)
MASTERC CDM-TC	15 mm	0.5 inch	7 mm	51 mm	53 mm	52 mm	85 mm
70W/830 G8.5							

Photometric data







Light Distribution Diagram - MASTERC CDM-TC 70W/830 G8.5

Spectral Power Distribution Colour - MASTERC CDM-TC 70W/830 G8.5

MASTERColour CDM-TC

Lifetime





Lumen Maintenance Diagram - MASTERC CDM-TC 70W/830 G8.5

Life Expectancy Diagram - MASTERC CDM-TC 70W/830 G8.5



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.