



MASTERColour CDM-TC

MASTERC CDM-TC 70W/830 G8.5

系列单端紧凑型高光效放电灯在整个寿命期间具有稳定的光色和明亮通透的闪光

安全提示

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般信息	
底盖	G8.5 [G8.5]
操作位置	UNIVERSAL [任意或通用 (U)]
50% 故障条件下的使用寿命 (标称)	12,000 小时

灯技术	
颜色代码	830 [CCT of 3000K]
颜色名称	暖白色 (WW)
色度坐标 X (标称)	0.439
色度坐标 Y (标称)	0.398
相关色温 (标称)	3000 K
光效 (额定) (标称)	86 lm/W
显色指数 (CRI)	83
弧长 O (标称)	7 mm

操作和电气	
功耗	73 W
电压 (标称)	83 V
电压 (标称)	83 V

控制和调光	
可调光	否

机械和外壳	
灯泡外观	透明
灯泡材料	防紫外线石英
灯泡外形	T14 [T 14 毫米]


审批和申请	
汞 (Hg) 含量 (标称)	4.6 mg

MASTERC colour CDM-TC

能耗 kWh/1000 h	80 kWh
产品数据	
订单产品名称	MASTERC CDM-TC 70W/830 G8.5
完整的产品名称	MASTERC CDM-TC 70W/830 G8.5
完整产品代码	871829118820900
订购代码	928086505105


材料编号 (12NC)	928086505105
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8718291188209
计算器 - 每个外包装箱中的包数	12
EAN/UPC - 案例	8718291188216

二维绘图




Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MASTERC CDM-TC 70W/830 G8.5	15 mm	0.5 in	7 mm	51 mm	53 mm	52 mm	85 mm

光度数据




Light Distribution Diagram - MASTERC CDM-TC 70W/830 G8.5




Spectral Power Distribution Colour - MASTERC CDM-TC 70W/830 G8.5

寿命



Lumen Maintenance Diagram - MASTERC CDM-TC 70W/830 G8.5



Life Expectancy Diagram - MASTERC CDM-TC 70W/830 G8.5

