



MASTER CosmoWhite CPO-TW

MST CosmoWh CPO-TW Xtra 60W/728 PGZ12

用于室外照明的新一代陶瓷金属卤化物灯使用新型灯座和透明石英外部灯泡生成白光

安全提示

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般信息	
底盖	PGZ12
操作位置	UNIVERSAL [任意或通用 (U)]
光通量测量参考	Sphere
50% 故障条件下的使用寿命 (标称)	32,000 小时
灯技术	
颜色代码	728 [CCT of 2800K]
光通量	7,200 lm
颜色名称	白色 (WH)
色度坐标 X (标称)	0.447
色度坐标 Y (标称)	0.4
相关色温 (标称)	2800 K
光效 (额定) (标称)	120 lm/W
显色指数 (CRI)	73


弧长 O (标称)	14 mm
操作和电气	
功耗	60.0 W
电压 (标称)	92 V
电压 (标称)	92 V
控制和调光	
可调光	是
机械和外壳	
灯泡外观	透明
灯泡外形	T19 [T 19 毫米]

MASTER CosmoWhite CPO-TW

审批和申请	
能效等级	E
汞 (Hg) 含量 (最高)	2 mg
汞 (Hg) 含量 (标称)	2.0 mg
能耗 kWh/1000 h	60 kWh
EPREL 注册号	473348
产品数据	
订单产品名称	MST CosmoWh CPO-TW Xtra 60W/728 PGZ12
完整的产品名称	MST CosmoWh CPO-TW Xtra 60W/728 PGZ12


完整产品代码	871150020851415
订购代码	928088505127
材料编号 (12NC)	928088505127
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8711500208514
计算器 - 每个外包装箱中的包数	12
EAN/UPC - 案例	8711500208521

二维绘图




Product	D (max)	D	O	L	C (max)
MST CosmoWh CPO-TW Xtra 60W/728 PGZ12	20 mm	19 mm	14 mm	59 mm	132 mm

光度数据




Light Distribution Diagram - MST CosmoWh CPO-TW Xtra 60W/728 PGZ12




Spectral Power Distribution Colour - MST CosmoWh CPO-TW Xtra 60W/728 PGZ12

MASTER CosmoWhite CPO-TW

寿命



Life Expectancy Diagram - MST CosmoWh CPO-TW Xtra 60W/728 PGZ12



Lumen Maintenance Diagram - MST CosmoWh CPO-TW Xtra 60W/728 PGZ12

