# **PHILIPS** Lighting



# MASTERColour CDM-R

# MASTERC CDM-R 70W/942 E27 PAR30L 40D 1CT

Range of compact, high-efficiency, discharge reflector lamps with a stable colour over lifetime and a crisp, sparkling light

#### Warnings and Safety

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. Color 830 lamps may also use electromagnetic gear.
- Use only with electronic control gear. Colour 830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**


General Information		Color rendering index (CRI)	93
Cap-Base	E27 [E27]	LLMF At End Of Nominal Lifetime (No	om) 61 %
Operating Position	UNIVERSAL [Any or Universal (U)]	Luminous Flux in 90° Cone (Rated)	3,800 lm
Switching Cycle	1,050		
Life to 50% Failures (Nom)	12,000 hour(s)	Operating and Electrical	
		Power Consumption	73 W
Light Technical		Warm-up time to 60% light	120 s
Color Code	942 [CCT of 4200K]	Voltage (Nom)	88 V
Beam Angle (Nom)	40 degree(s)	Voltage (Nom)	88 V
Luminous Intensity (Nom)	9,000 cd		
Color Designation	Cool White (CW)	Controls and Dimming	
Chromaticity Coordinate X (Nom)	0.371	Dimmable	No
Chromaticity Coordinate Y (Nom)	0.366		
Correlated Color Temperature (Nom)	4200 K		

# MASTERColour CDM-R


Mechanical and Housing				
Bulb Finish	Clear			
Bulb Shape	PAR30L [PAR 3.75 inch/95mm Long]			
Approval and Application				
Mercury (Hg) Content (Nom)	6.6 mg			
Energy Consumption kWh/1000 h	80 kWh			
Product Data				
Order product name	MASTERC CDM-R 70W/942 E27 PAR30L 40D			
	1CT			

Full product name	MASTERC CDM-R 70W/942 E27 PAR30L 40D			
	1CT			
Full product code	871150021178100			
Order code	928089400691			
Material Nr. (12NC)	928089400691			
Numerator - Quantity Per Pack	1			
EAN/UPC - Product/Case	8711500211781			
Numerator - Packs per outer box	6			
EAN/UPC - Case	8711500211798			

## **Dimensional drawing**




#### Photometric data



Light Distribution Diagram - MASTERC CDM-R 70W/942 E27 PAR30L 40D 1CT

Product	D (max)	D	C (max)	с
MASTERC CDM-R 70W/942 E27 PAR30L 40D 1CT	97 mm	95 mm	123 mm	120 mm




Spectral Power Distribution Colour - MASTERC CDM-R 70W/942 E27 PAR30L 40D 1CT

# **MASTERColour CDM-R**

Life Expectancy Diagram - MASTERC CDM-R 70W/942 E27 PAR30L 40D

## Lifetime

1CT



Lumen Maintenance Diagram - MASTERC CDM-R 70W/942 E27 PAR30L 40D 1CT



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.