

MASTERColour CDM-R

MASTERC CDM-R 70W/942 E27 PAR30L 30D 1CT

Range of compact, high-efficiency, discharge reflector lamps with a stable colour over lifetime and a crisp, sparkling light

Warnings and Safety

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. Colour 830 lamps may also use electromagnetic gear.

Product data

General Information	
Cap-Base	E27 [E27]
Operating Position	UNIVERSAL [Any or Universal (U)]
Switching Cycle	1,050
Life to 50% Failures (Nom)	12,000 hour(s)

Light Technical	
Color Code	942 [CCT of 4200K]
Beam Angle (Nom)	30 degree(s)
Luminous Intensity (Nom)	13,000 cd
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	0.371
Chromaticity Coordinate Y (Nom)	0.366
Correlated Color Temperature (Nom)	4200 K
Color rendering index (CRI)	93
LLMF At End Of Nominal Lifetime (Nom)	61 %
Luminous Flux in 90° Cone (Rated)	4,000 lm

Operating and Electrical	
Power Consumption	73 W
Warm-up time to 60% light	120 s
Voltage (Nom)	88 V
Voltage (Nom)	88 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	PAR30L [PAR 3.75 inch/95mm Long]


Approval and Application	
Mercury (Hg) Content (Nom)	6.6 mg
Energy Consumption kWh/1000 h	80 kWh

MASTERColour CDM-R

Product Data	
Order product name	MASTERC CDM-R 70W/942 E27 PAR30L 30D 1CT
Full product name	MASTERC CDM-R 70W/942 E27 PAR30L 30D 1CT
Full product code	871150021180400
Order code	928089700691


Material Nr. (12NC)	928089700691
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500211804
Numerator - Packs per outer box	6
EAN/UPC - Case	8711500211811

Dimensional drawing




Product	D (max)	D	C (max)	C
MASTERC CDM-R 70W/942 E27 PAR30L 30D 1CT	97 mm	95 mm	123 mm	120 mm

Photometric data




Light Distribution Diagram - MASTERC CDM-R 70W/942 E27 PAR30L 30D 1CT




Spectral Power Distribution Colour - MASTERC CDM-R 70W/942 E27 PAR30L 30D 1CT

MASTERColour CDM-R

Lifetime



Life Expectancy Diagram - MASTERC CDM-R 70W/942 E27 PAR30L 30D 1CT



Lumen Maintenance Diagram - MASTERC CDM-R 70W/942 E27 PAR30L 30D 1CT

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.