



MASTERColour CDM-T

MASTERC CDM-T 250W/942 G12 1CT/12

Range of single-ended, compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light

Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- \cdot Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information					
Cap-Base	G12				
Operating Position	UNIVERSAL [Any or Universal (U)]				
Flux measurement reference	Sphere				
Life to 50% Failures (Nom)	15,000 hour(s)				
Light Technical					
Color Code	942 [CCT of 4200K]				
Luminous Flux	26,250 lm				
Color Designation	Cool White (CW)				
Chromaticity Coordinate X (Nom)	0.371				
Chromaticity Coordinate Y (Nom)	0.366				
Correlated Color Temperature (Nom)	4200 K				

Luminous Efficacy (rated) (Nom)	105 lm/W
Color rendering index (CRI)	91
Arc Length O (Nom)	12.3 mm
Operating and Electrical	
Power Consumption	250.0 W
Voltage (Nom)	93 V
Voltage (Nom)	93 V
Controls and Dimming	
Dimmable	No


Datasheet, 2023, April 14 data subject to change

MASTERColour CDM-T

Mechanical and Housing						
Bulb Finish	Clear					
Bulb Shape	T24					
Approval and Application						
Energy Efficiency Class	F					
Mercury (Hg) Content (Max)	20 mg					
Mercury (Hg) Content (Nom)	20.0 mg					
Energy Consumption kWh/1000 h	250 kWh					
EPREL Registration Number	473354					
Product Data						
Order product name	MASTERC CDM-T 250W/942 G12 1CT/12					


Full product name	MASTERC CDM-T 250W/942 G12 1CT/12				
Full product code	871150021112515				
Order code	928094205131				
Material Nr. (12NC)	928094205131				
Numerator - Quantity Per Pack	1				
EAN/UPC - Product/Case	8711500211125				
Numerator - Packs per outer box	12				
EAN/UPC - Case	8711500211132				


Dimensional drawing




Product	D (max)	0	L (min)	L (max)	L	C (max)
MASTERC CDM-T 250W/942	25 mm	12.3 mm	71.5 mm	73.5 mm	72.5 mm	135 mm
G12 1CT/12						

Photometric data









Light Distribution Diagram - MASTERC CDM-T 250W/942 G12 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-T 250W/942 G12 1CT/12

MASTERColour CDM-T

Lifetime





Lumen Maintenance Diagram - MASTERC CDM-T 250W/942 G12 1CT/12

Life Expectancy Diagram - MASTERC CDM-T 250W/942 G12 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.