PHILIPS Lighting



MASTERColour CDM-R111

MASTERC CDM-R111 70W/942 GX8.5 40D 1CT/6

The MASTERColour CDM-R111 combines the trendy look of 111 mm aluminum reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

Warnings and Safety

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- \cdot Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		LLMF At End Of Nominal Lifetime (Nom) 60 %	
Cap-Base	GX8.5	Luminous Flux in 90° Cone (Rated)	2,800 lm
Operating Position	UNIVERSAL [Any or Universal (U)]		
Switching Cycle	1,000	Operating and Electrical	
Life to 50% Failures (Nom)	11,000 hour(s)	Power Consumption	73.2 W
		Warm-up time to 60% light	120 s
Light Technical		Voltage (Nom)	92 V
Color Code	942 [CCT of 4200K]	Voltage (Nom)	92 V
Beam Angle (Nom)	40 degree(s)		
Luminous Intensity (Nom)	6,700 cd	Controls and Dimming	
Color Designation	Cool White (CW)	Dimmable	No
Chromaticity Coordinate X (Nom)	0.381		
Chromaticity Coordinate Y (Nom)	0.370	Mechanical and Housing	
Correlated Color Temperature (Nom)	4200 K	Bulb Finish	Reflector
Color rendering index (CRI)	96		

MASTERColour CDM-R111


Bulb Shape	R111		
Approval and Application			
Energy Efficiency Class	G		
Mercury (Hg) Content (Nom)	6.3 mg		
Energy Consumption kWh/1000 h	80 kWh		
Product Data			
Order product name	MASTERC CDM-R111 70W/942 GX8.5 40D		
	1CT/6		
Full product name	MASTERC CDM-R111 70W/942 GX8.5 40D		
	1CT/6		

Full product code	871150021395210
Order code	928098105330
Material Nr. (12NC)	928098105330
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500213952
Numerator - Packs per outer box	6
EAN/UPC - Case	8711500213969

Dimensional drawing




Photometric data



Light Distribution Diagram - MASTERC CDM-R111 70W/942 GX8.5 40D 1CT/6


Product	D (max)	C (max)
MASTERC CDM-R111 70W/942 GX8.5 40D 1CT/6	111 mm	95 mm



Spectral Power Distribution Colour - MASTERC CDM-R111 70W/942 GX8.5 40D 1CT/6

MASTERColour CDM-R111

Lifetime



Life Expectancy Diagram - MASTERC CDM-R111 70W/942 GX8.5 40D 1CT/6

\$° 100 60 40 20 0 0 0 3000 6000 9000 12000 Burning hours

Lumen Maintenance Diagram - MASTERC CDM-R111 70W/942 GX8.5 40D 1CT/6



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.