

Architectural MSA

MSA 2500 DE UNP/1

The high luminous efficacy and optimal lamp filling of the double ended Architectural MSA lamps create high beam intensity and excellent color rendering. While the compact arc of the lamp allows efficient beam control and high intensity. Ideal to illuminate architecture of all types at night.

安全提示

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般信息	
底盖	(P)SFC [(P)SFC]
操作位置	P15 [并行 +/-15D 或水平 (HOR)]
50% 故障条件下的使用寿命 (标称)	2,500 小时

灯技术	
颜色代码	856
光通量	250,000 lm
色度坐标 X (标称)	330
色度坐标 Y (标称)	360
相关色温 (标称)	5600 K
光效 (额定)(标称)	100 lm/W
显色指数 (CRI)	88
弧长 O (标称)	25 mm


操作和电气	
功耗	2,500 W
灯具电流 (标称)	22.5 A

控制和调光	
可调光	否

产品数据	
订单产品名称	MSA 2500 DE UNP/1
完整的产品名称	MSA 2500 DE UNP/1
完整产品代码	871150020208600
订购代码	928099405103
材料编号 (12NC)	928099405103
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8718291548300
计算器 - 每个外包装箱中的包数	1
EAN/UPC - 案例	8711500202086


Architectural MSA

二维绘图



Product	D (max)	O	C (max)
MSA 2500 DE UNP/1	41 mm	25 mm	364 mm

光度数据



Spectral Power Distribution Colour - MSA 2500 DE UNP/1

© 2023 Signify Holding 保留所有权利。 Signify 对此文档所包含信息的准确性或完整性不作任何陈述或保证，也不对根据此文档信息做出的任何行为负责。 本文档中提供的信息不作为任何商业要约，也不构成任何报价或合同的一部分，除非 Signify 同意。
Philips 和 Philips Shield Emblem 是 Koninklijke Philips N.V. 的注册商标。