



# MasterColor CDM-T T6

## MasterColor CDM-T 35W/842 T6

MasterColor CDM lamp gives a unique combination of unbeatable light quality and consistent performance over lifetime while keeping running costs low. The Philips MasterColor Tubular Single-Ended T6 lamp is a compact, energy efficient, ceramic metal halide lamp that provides crisp, sparkling light.

#### Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)
- · Lamp contains mercury.
- · Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

#### **Product data**

| General Information                |                                  |  |  |  |  |
|------------------------------------|----------------------------------|--|--|--|--|
| Cap-Base                           | G12 [G12]                        |  |  |  |  |
| Operating Position                 | UNIVERSAL [Any or Universal (U)] |  |  |  |  |
| Life to 50% Failures (Nom)         | 12,000 hour(s)                   |  |  |  |  |
|                                    |                                  |  |  |  |  |
| Light Technical                    |                                  |  |  |  |  |
| Color Code                         | 842 [CCT of 4200K]               |  |  |  |  |
| Color Designation                  | Cool White (CW)                  |  |  |  |  |
| Chromaticity Coordinate X (Nom)    | 0.365                            |  |  |  |  |
| Chromaticity Coordinate Y (Nom)    | 0.364                            |  |  |  |  |
| Correlated Color Temperature (Nom) | 4200 K                           |  |  |  |  |
|                                    |                                  |  |  |  |  |

| Luminous Efficacy (rated) (Nom) | 79 lm/W |
|---------------------------------|---------|
| Color rendering index (CRI)     | 84      |
| Arc Length O (Nom)              | 5 mm    |
|                                 |         |
| Operating and Electrical        |         |
| Power Consumption               | 35 W    |
| Voltage (Nom)                   | 85 V    |
| Voltage (Nom)                   | 85 V    |
|                                 |         |


Datasheet, 2023, April 29 data subject to change

## MasterColor CDM-T T6

| Controls and Dimming          |              |  |
|-------------------------------|--------------|--|
| Dimmable                      | No           |  |
|                               |              |  |
| Mechanical and Housing        |              |  |
| Bulb Finish                   | Clear        |  |
| Bulb Shape                    | T19 [T 19mm] |  |
|                               |              |  |
| Approval and Application      |              |  |
| Mercury (Hg) Content (Nom)    | 2.7 mg       |  |
| Energy Consumption kWh/1000 h | 41 kWh       |  |


| Product Data                    |                              |  |  |  |
|---------------------------------|------------------------------|--|--|--|
| Order product name              | CDM-T 35W/842 T6             |  |  |  |
| Full product name               | MasterColor CDM-T 35W/842 T6 |  |  |  |
| Order code                      | 208868                       |  |  |  |
| Material Nr. (12NC)             | 928099805115                 |  |  |  |
| Numerator - Quantity Per Pack   | 1                            |  |  |  |
| EAN/UPC - Product/Case          | 046677208868                 |  |  |  |
| Numerator - Packs per outer box | 12                           |  |  |  |
| EAN/UPC - Case                  | 50046677208863               |  |  |  |


## Dimensional drawing





| Product          | D (max) | D         | 0    | L (min) | L (max) | L     | C (max) |
|------------------|---------|-----------|------|---------|---------|-------|---------|
| CDM-T 35W/842 T6 | 20 mm   | 0.75 inch | 5 mm | 55 mm   | 57 mm   | 56 mm | 103 mm  |

#### Photometric data











Light Distribution Diagram - CDM-T 35W/842 T6


Light Distribution Diagram - CDM-T 35W/842 T6


## MasterColor CDM-T T6

#### Photometric data












#### Light Distribution Diagram - CDM-T 35W/842 T6

Light Distribution Diagram - CDM-T 35W/842 T6








Light Distribution Diagram - CDM-T 35W/842 T6

Spectral Power Distribution Colour - CDM-T 35W/842 T6

#### Lifetime



Life Expectancy Diagram - CDM-T 35W/842 T6

## MasterColor CDM-T T6



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.