



# MASTERColour CDM-R Elite

## MC CDM-R Elite 50W/930 E27 PAR30L 30D

Compact, very high-efficiency, long-life Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

### Warnings and Safety

- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data


General Information		LLMF At End Of Nominal Lifetime (Nom)	
Cap-Base	E27 [E27]	Luminous Flux in 90° Cone (Rated)	80 %
Operating Position	UNIVERSAL [Any or Universal (U)]		3,200 lm
Switching Cycle	1,350	Operating and Electrical	
Life to 50% Failures (Nom)	15,000 hour(s)	Power Consumption	50 W
		Warm-up time to 60% light	120 s
Light Technical		Voltage (Nom)	89 V
Color Code	930 [CCT of 3000K]	Voltage (Nom)	89 V
Beam Angle (Nom)	30 degree(s)	Controls and Dimming	
Luminous Intensity (Nom)	11,000 cd	Dimmable	No
Color Designation	Warm White (WW)	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	0.437	Bulb Finish	Clear
Chromaticity Coordinate Y (Nom)	0.400	Bulb Shape	PAR30L [PAR 3.75 inch/95mm Long]
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	72 lm/W		
Color rendering index (CRI)	91		

MASTERC colour CDM-R Elite

Approval and Application	
Mercury (Hg) Content (Nom)	6.6 mg
Energy Consumption kWh/1000 h	55 kWh
Product Data	
Order product name	MC CDM-R Elite 50W/930 E27 PAR30L 30D
Full product name	MC CDM-R Elite 50W/930 E27 PAR30L 30D
Full product code	871829124198000



Order code	928108600630
Material Nr. (12NC)	928108600630
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291241980
Numerator - Packs per outer box	6
EAN/UPC - Case	8718291241997

Dimensional drawing



Product	D (max)	C (max)
MC CDM-R Elite 50W/930 E27 PAR30L 30D	97 mm	123 mm

Photometric data




Light Distribution Diagram - MC CDM-R Elite 50W/930 E27 PAR30L 30D

Spectral Power Distribution Colour - MC CDM-R Elite 50W/930 E27 PAR30L 30D

MASTERColour CDM-R Elite

Lifetime



Life Expectancy Diagram - MC CDM-R Elite 50W/930 E27 PAR30L 30D

Lumen Maintenance Diagram - MC CDM-R Elite 50W/930 E27 PAR30L 30D

