



MASTER SOX-E

MASTER SOX-E 18W BY22d 1SL/12

Low Pressure Sodium lamp with improved efficacy

Warnings and Safety

- Lamps may use electronic or electromagnetic control gear

Product data


General Information	
Cap-Base	BY22D [BY22d]
Operating Position	H110 [Hanging +/-110D or Base Up (BU)]
Life to 50% Failures (Nom)	18,000 hour(s)
Light Technical	
Correlated Color Temperature (Nom)	1800 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Operating and Electrical	
Power Consumption	18.0 W
Voltage (Nom)	57 V
Voltage (Nom)	57 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	T50 [T 50mm]

Approval and Application	
Mercury (Hg) Content (Nom)	0 mg
Energy Consumption kWh/1000 h	21 kWh
Product Data	
Order product name	MASTER SOX-E 18W BY22d 1SL/12
Full product name	MASTER SOX-E 18W BY22d 1SL/12
Full product code	871150019280615
Order code	19280615
Material Nr. (12NC)	928145200008
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500192806
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500193407


MASTER SOX-E

Dimensional drawing

Product	D (max)	C (max)
MASTER SOX-E 18W BY22d 1SL/12	52 mm	216 mm




Photometric data



Light Distribution Diagram - MASTER SOX-E 18W BY22d 1SL/12

Lifetime



Life Expectancy Diagram - MASTER SOX-E 18W BY22d 1SL/12

Lumen Maintenance Diagram - MASTER SOX-E 18W BY22d 1SL/12

