



MASTER SDW-TG 小型

MST SDW-TG Mini 50W/825 GX12-1 1CT/12

系列高光效放电灯,用于 MASTERColour CDM-T 光源的小型开放式灯具

安全提示

- Use only with dedicated Philips control gear
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般信息	
底盖	GX12-1 [GX12-1]
操作位置	UNIVERSAL [任意或通用 (U)]
光通量测量参考	Sphere
50% 故障条件下的使用寿命 (标称)	10,000 小时
灯技术	
颜色代码	825 [CCT of 2500K]
光通量	2,400 lm
颜色名称	金白色
色度坐标 x (标称)	0.478
色度坐标 y (标称)	0.415
相关色温 (标称)	2500 K
光效 (额定) (标称)	44 lm/W
显色指数 (CRI)	81
弧长 O (标称)	14 mm
操作和电气	
功耗	54.0 W
电压 (标称)	85 V


电压 (标称)	85 V
控制和调光	
可调光	否
机械和外壳	
灯泡外观	透明
灯泡材料	玻璃
灯泡外形	T19 [T 19 毫米]
审批和申请	
能效等级	G
汞 (Hg) 含量 (最高)	5.7 mg
汞 (Hg) 含量 (标称)	5.7 mg
能耗 kWh/1000 h	54 kWh
EPREL 注册号	473250
产品数据	
订单产品名称	MST SDW-TG Mini 50W/825 GX12-1 1CT/12
完整的产品名称	MST SDW-TG Mini 50W/825 GX12-1 1CT/12

MASTER SDW-TG 小型

完整产品代码	871150020323615
订购代码	928159905131
材料编号 (12NC)	928159905131
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8711500203236


计算器 - 每个外包装箱中的包数	12
EAN/UPC - 案例	8711500203243

二维绘图




Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MST SDW-TG Mini	20 mm	0.75 in	14.5 mm	53.5 mm	56.5 mm	55 mm	103 mm
50W/825 GX12-1 1CT/12							

光度数据




Spectral Power Distribution Colour - MST SDW-TG Mini 50W/825 GX12-1 1CT/12

寿命



Life Expectancy Diagram - MST SDW-TG Mini 50W/825 GX12-1 1CT/12



Lumen Maintenance Diagram - MST SDW-TG Mini 50W/825 GX12-1 1CT/12

MASTER SDW-TG 小型

