



MASTERColour CDM-Tm Elite Mini

MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT

Mini, single-ended, very high-efficiency, long-life Ceramic Metal Halide discharge lamp producing crisp white sparkling light with high colour rendering

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- For 50W use with Philips electronic gear only
- Control gear must include end-of-life protection (IEC61167, IEC 62035)

Product data

General Information		Arc Length O (Nom)	
Cap-Base	GU6.5	3.4 mm	
Operating Position	UNIVERSAL [Any or Universal (U)]		
Flux measurement reference	Sphere		
Life to 50% Failures (Nom)	20,000 hour(s)		
Light Technical		Operating and Electrical	
Color Code	830 [CCT of 3000K]	Power Consumption	20.1 W
Luminous Flux	1,800 lm	Voltage (Nom)	95 V
Color Designation	Warm White (WW)	Voltage (Nom)	95 V
Chromaticity Coordinate X (Nom)	0.434		
Chromaticity Coordinate Y (Nom)	0.398		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	90 lm/W		
Color rendering index (CRI)	84		
		Controls and Dimming	
		Dimmable	No
		Mechanical and Housing	
		Bulb Finish	Clear
		Bulb Shape	T-4
		Approval and Application	
		Energy Efficiency Class	G

MASTERColour CDM-Tm Elite Mini


Mercury (Hg) Content (Max)	3.5 mg
Mercury (Hg) Content (Nom)	3.5 mg
Energy Consumption kWh/1000 h	21 kWh
EPREL Registration Number	473256

Product Data

Order product name	MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT
Full product name	MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT
Full product code	872790089083900

Order code	928183505130
Material Nr. (12NC)	928183505130
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900890839
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900890846

Dimensional drawing




Product	D (max)	D	O	L (min)	L (max)	L	C (max)
MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT	13.3 mm	0.5 inch	3.4 mm	28 mm	32 mm	30 mm	56.7 mm

Photometric data





Light Distribution Diagram - MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT



Spectral Power Distribution Colour - MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT

MASTERColour CDM-Tm Elite Mini

Lifetime



Life Expectancy Diagram - MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT

Lumen Maintenance Diagram - MC CDM-Tm Elite Mini 20W/830 GU6.5 1CT

