

MASTERColour CDM-TC 精锐型

MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

单端、外型紧凑且高效的陶瓷金卤放电光源

安全提示

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

一般信息	
底盖	G8.5 [G8.5]
操作位置	UNIVERSAL [任意或通用 (U)]
50% 故障条件下的使用寿命 (标称)	20,000 小时

灯技术	
颜色代码	930 [CCT of 3000K]
颜色名称	暖白色 (WW)
色度坐标 X (标称)	0.435
色度坐标 Y (标称)	0.396
相关色温 (标称)	3000 K
光效 (额定)(标称)	107 lm/W
显色指数 (CRI)	90
弧长 O (标称)	7.15 mm

操作和电气	
功耗	73.0 W
电压 (标称)	85 V
电压 (标称)	85 V

控制和调光	
可调光	否

机械和外壳	
灯泡外观	透明
灯泡外形	T14 [T 14 毫米]

审批和申请	
汞 (Hg) 含量 (标称)	6.6 mg


MASTERColour CDM-TC 精锐型

能耗 kWh/1000 h	80 kWh

产品数据	
订单产品名称	MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12
完整的产品名称	MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12
完整产品代码	871869643732200
订购代码	928189505105


材料编号 (12NC)	928189505105
计算器 - 每包数量	1
EAN/UPC - 产品/箱	8718696437322
计算器 - 每个外包装箱中的包数	12
EAN/UPC - 案例	8718696437339

二维绘图





Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12	15 mm	7.15 mm	51 mm	53 mm	52 mm	85 mm

光度数据



Light Distribution Diagram - MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12






Spectral Power Distribution Colour - MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

MASTERColour CDM-TC 精锐型

寿命





Lumen Maintenance Diagram - MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

Life Expectancy Diagram - MASTERC CDM-TC Elite 70W/930 G8.5 1CT/12

© 2023 Signify Holding 保留所有权利。 Signify 对此文档所包含信息的准确性或完整性不作任何陈述或保证，也不对根据此文档信息做出的任何行为负责。 本文档中提供的信息不作为任何商业要约，也不构成任何报价或合同的一部分，除非 Signify 同意。 Philips 和 Philips Shield Emblem 是 Koninklijke Philips N.V. 的注册商标。