

MASTERColour CDM-Rm Elite Mini

CDM-Rm Elite Mini 35W/942 GX10 MR16 40D

Mini, very high-efficiency Ceramic Metal Halide discharge reflector lamp producing crisp white sparkling light with high color rendering

Warnings and Safety

- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035).
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	GX10 [GX10]
Operating Position	UNIVERSAL [Any or Universal (U)]
Switching Cycle	1,350
Life to 50% Failures (Nom)	15,000 hour(s)

Light Technical	
Color Code	942 [CCT of 4200K]
Beam Angle (Nom)	40 degree(s)
Luminous Intensity (Nom)	3,400 cd
Chromaticity Coordinate X (Nom)	0.377
Chromaticity Coordinate Y (Nom)	0.377
Correlated Color Temperature (Nom)	4200 K
Luminous Efficacy (rated) (Nom)	57.5 lm/W
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	73 %
Luminous Flux in 90° Cone (Rated)	2,000 lm

Operating and Electrical	
Power Consumption	39 W
Warm-up time to 60% light	120 s
Voltage (Nom)	90 V
Voltage (Nom)	90 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Shape	MR16 [2inch/50mm]

Approval and Application	
Mercury (Hg) Content (Nom)	4.7 mg

MASTERColour CDM-Rm Elite Mini


Energy Consumption kWh/1000 h	43 kWh

Material Nr. (12NC)	928193505330
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291691815
Numerator - Packs per outer box	12
EAN/UPC - Case	8718291691822

Product Data


Order product name	CDM-Rm Elite Mini 35W/942 GX10 MR16 40D
Full product name	CDM-Rm Elite Mini 35W/942 GX10 MR16 40D
Full product code	871829169181500
Order code	928193505330

Dimensional drawing




Product	D (max)	D	C (max)	C	C1 (max)	A (max)
CDM-Rm Elite Mini 35W/942 GX10 MR16 40D	51 mm	50 mm	65.4 mm	62.75 mm	60.9 mm	59 mm

Photometric data




Light Distribution Diagram - CDM-Rm Elite Mini 35W/942 GX10 MR16 40D



Spectral Power Distribution Colour - CDM-Rm Elite Mini 35W/942 GX10 MR16 40D

MASTERColour CDM-Rm Elite Mini

Lifetime



Life Expectancy Diagram - CDM-Rm Elite Mini 35W/942 GX10 MR16 40D

Lumen Maintenance Diagram - CDM-Rm Elite Mini 35W/942 GX10 MR16 40D

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.