



# MasterColor CDM-R111 Elite

## MASTERC CDM-R111 Elite 35W/930 GX8.5 10D

MasterColor CDM-R111 Elite combines the trendy look of 111 mm aluminum-reflector halogen lamps with the long life, high energy efficiency and crisp white light of MasterColor CDM.

### Warnings and Safety

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/930 lamps may also use electromagnetic gear
- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

### Product data

General Information		Correlated Color Temperature (Nom)	
Cap-Base	GX8.5	Correlated Color Temperature (Nom)	3000 K
Operating Position	UNIVERSAL [Any or Universal (U)]	Luminous Efficacy (rated) (Nom)	37 lm/W
Switching Cycle	1,050	Color rendering index (CRI)	90
Life to 50% Failures (Nom)	12,000 hour(s)	LLMF At End Of Nominal Lifetime (Nom)	70 %
Light Technical		Luminous Flux in 90° Cone (Rated)	1,350 lm
Color Code	930 [CCT of 3000K]	Operating and Electrical	
Beam Angle (Nom)	10 degree(s)	Power Consumption	39.1 W
Luminous Intensity (Nom)	36,000 cd	Warm-up time to 60% light	120 s
Color Designation	Warm White (WW)	Voltage (Nom)	89 V
Chromaticity Coordinate X (Nom)	0.432	Voltage (Nom)	89 V
Chromaticity Coordinate Y (Nom)	0.392		

# MasterColor CDM-R111 Elite

## Controls and Dimming

Dimmable	No
----------	----

## Mechanical and Housing

Bulb Finish	Reflector
Bulb Shape	R111


## Approval and Application

Mercury (Hg) Content (Nom)	4.7 mg
Energy Consumption kWh/1000 h	43 kWh

## Product Data



Order product name	MASTERC CDM-R111 Elite 35W/930 GX8.5 10D
Full product name	MASTERC CDM-R111 Elite 35W/930 GX8.5 10D
Order code	928195305306
Material Nr. (12NC)	928195305306
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677430726
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677430721

## Dimensional drawing



Product	D (max)	C (max)
MASTERC CDM-R111 Elite 35W/930 GX8.5 10D	111 mm	95 mm

## Photometric data



Spectral Power Distribution Colour - MASTERC CDM-R111 Elite 35W/930 GX8.5 10D

Light Distribution Diagram - MASTERC CDM-R111 Elite 35W/930 GX8.5 10D

## MasterColor CDM-R111 Elite

