Lighting

PHILIPS



A ↑ G

G

MASTERColour CDM-R111 Elite

MASTERC CDM-R111 Elite 35W/930 GX8.5 24D

MASTERColour CDM-R111 Elite combines the trendy look of 111 mm aluminumreflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

Warnings and Safety

- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/930 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General Information | | Correlated Color Temperature (Nom) | 3000 K |
|---------------------------------|----------------------------------|--------------------------------------|----------|
| Cap-Base | GX8.5 | Luminous Efficacy (rated) (Nom) | 46 lm/W |
| Operating Position | UNIVERSAL [Any or Universal (U)] | Color rendering index (CRI) | 90 |
| Switching Cycle | 1,050 | LLMF At End Of Nominal Lifetime (Non | n) 70 % |
| Flux measurement reference | Narrow Cone | Luminous Flux in 90° Cone (Rated) | 1,750 lm |
| Life to 50% Failures (Nom) | 12,000 hour(s) | | |
| | | Operating and Electrical | |
| Light Technical | | Power Consumption | 39.1 W |
| Color Code | 930 [CCT of 3000K] | Warm-up time to 60% light | 120 s |
| Beam Angle (Nom) | 24 degree(s) | Voltage (Nom) | 89 V |
| Luminous Flux | 1,750 lm | Voltage (Nom) | 89 V |
| Luminous Intensity (Nom) | 8,500 cd | | |
| Color Designation | Warm White (WW) | Controls and Dimming | |
| Chromaticity Coordinate X (Nom) | 0.434 | Dimmable | No |
| Chromaticity Coordinate Y (Nom) | 0.398 | | |

MASTERColour CDM-R111 Elite


| Mechanical and Housing | |
|-------------------------------|-----------|
| Bulb Finish | Reflector |
| Bulb Shape | R111 |
| | |
| Approval and Application | |
| Energy Efficiency Class | G |
| Mercury (Hg) Content (Max) | 4.7 mg |
| Mercury (Hg) Content (Nom) | 4.7 mg |
| Energy Consumption kWh/1000 h | 40 kWh |
| EPREL Registration Number | 473280 |
| | |
| Product Data | |

MASTERC CDM-R111 Elite 35W/930 GX8.5 24D

| Full product name | MASTERC CDM-R111 Elite 35W/930 GX8.5 24E | |
|---------------------------------|--|--|
| Full product code | 871829168944700 | |
| Order code | 928195405330 | |
| Material Nr. (12NC) | 928195405330 | |
| Numerator - Quantity Per Pack | 1 | |
| EAN/UPC - Product/Case | 8718291689447 | |
| Numerator - Packs per outer box | 6 | |
| EAN/UPC - Case | 8718291689454 | |

Dimensional drawing

Order product name




| MASTERC CDM-R111 Elite 35W/930 GX8.5 24D | 111 mm | 95 mm |
|--|--------|-------|
| | | |


D (max)

C (max)

Photometric data



Spectral Power Distribution Colour - MASTERC CDM-R111 Elite 35W/930 GX8.5 24D



Product

Light Distribution Diagram - MASTERC CDM-R111 Elite 35W/930 GX8.5 24D

MASTERColour CDM-R111 Elite



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2024, March 21 - data subject to change