



MASTERColour CDM-R111 Elite



MASTERC CDM-R111 Elite 35W/930 GX8.5 40D

MASTERColour CDM-R111 Elite combines the trendy look of 111 mm aluminum-reflector halogen lamps with the long life, high energy efficiency and crisp white light of MASTERColour CDM.

Warnings and Safety

- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Use only with electronic control gear. 35W/930 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	GX8.5
Operating Position	UNIVERSAL [Any or Universal (U)]
Switching Cycle	1,050
Flux measurement reference	Narrow Cone
Life to 50% Failures (Nom)	12,000 hour(s)
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	40 degree(s)
Luminous Flux	1,750 lm
Luminous Intensity (Nom)	4,500 cd
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.434
Chromaticity Coordinate Y (Nom)	0.398

Correlated Color Temperature (Nom)	3000 K	
Luminous Efficacy (rated) (Nom)	46 lm/W	
Color rendering index (CRI)	90	
LLMF At End Of Nominal Lifetime (Nom) 70 %		
Luminous Flux in 90° Cone (Rated)	1,750 lm	
Operating and Electrical		
Power Consumption	39.1 W	
Warm-up time to 60% light	120 s	
Voltage (Nom)	89 V	
Voltage (Nom)	89 V	
Controls and Dimming		
Dimmable	No	


Datasheet, 2024, March 21 data subject to change

MASTERColour CDM-R111 Elite

Mechanical and Housing		
Bulb Finish	Reflector	
Bulb Shape	R111	
Approval and Application		
Energy Efficiency Class	G	
Mercury (Hg) Content (Max)	4.7 mg	
Mercury (Hg) Content (Nom)	4.7 mg	
Energy Consumption kWh/1000 h	40 kWh	
EPREL Registration Number	473281	
Product Data		
Order product name	MASTERC CDM-R111 Elite 35W/930 GX8.5 40D	


Full product name	MASTERC CDM-R111 Elite 35W/930 GX8.5 40D
Full product code	871829168952200
Order code	928195505330
Material Nr. (12NC)	928195505330
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291689522
Numerator - Packs per outer box	6
EAN/UPC - Case	8718291689539


Dimensional drawing




Product	D (max)	C (max)
MASTERC CDM-R111 Elite 35W/930 GX8.5 40D	111 mm	95 mm

Photometric data







Light Distribution Diagram - MASTERC CDM-R111 Elite 35W/930 GX8.5 40D

MASTERColour CDM-R111 Elite



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.