



# MasterColor CDM-R111 Elite

# MASTERColor CDM-R111 Elite 70W/930 GX8.5 24D

MasterColor CDM-R111 Elite combines the trendy look of 111 mm aluminum-reflector halogen lamps with the long life, high energy efficiency and crisp white light of MasterColor CDM.

#### **Warnings and Safety**

- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- · Use only with electronic control gear. 35W/930 lamps may also use electromagnetic gear
- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

#### **Product data**

General Information	
Cap-Base	GX8.5 [GX8.5]
Operating Position	UNIVERSAL [Any or Universal (U)]
Switching Cycle	1,050
Life to 50% Failures (Nom)	12,000 hour(s)
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	24 degree(s)
Luminous Intensity (Nom)	16,000 cd
Color Designation	Warm White (WW)

Chromaticity Coordinate X (Nom)	0.441
Chromaticity Coordinate Y (Nom)	0.397
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	50 lm/W
Color rendering index (CRI)	92
LLMF At End Of Nominal Lifetime (Nom	n) 70 %
Luminous Flux in 90° Cone (Rated)	3,550 lm
Operating and Electrical	
Power Consumption	73.2 W
Warm-up time to 60% light	120 s


Datasheet, 2023, April 16 data subject to change

## MasterColor CDM-R111 Elite

Voltage (Nom)	89 V
Voltage (Nom)	89 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Reflector
Bulb Shape	R111 [R 111mm]
Approval and Application	
Mercury (Hg) Content (Nom)	6.6 mg
Energy Consumption kWh/1000 h	80 kWh


Product Data	
Order product name	MASTERC CDM-R111 Elite 70W/930 GX8.5 24D
Full product name	MASTERColor CDM-R111 Elite 70W/930 GX8.5
	24D
Order code	430769
Material Nr. (12NC)	928195705306
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677430764
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677430769


## Dimensional drawing




Product	D (max)	C (max)
MASTERC CDM-R111 Elite 70W/930 GX8.5 24D	111 mm	95 mm

#### Photometric data







Light Distribution Diagram - MASTERC CDM-R111 Elite 70W/930 GX8.5 24D

## MasterColor CDM-R111 Elite



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.