



# MASTERCoulour CDM-T Fresh

## MASTERCoulour CDM-T Fresh 70W/740 G12 1CT

Single-ended, high-efficiency Ceramic Metal Halide discharge lamp with special color enhancement properties

### Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data


General Information	
Cap-Base	G12 [G12]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	15,000 hour(s)
Light Technical	
Color Code	740 [CCT of 4000K]
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	0.380
Chromaticity Coordinate Y (Nom)	0.382
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	82 lm/W
Color rendering index (CRI)	70
Arc Length O (Nom)	7.15 mm
Operating and Electrical	
Power Consumption	73.0 W
Voltage (Nom)	83 V
Voltage (Nom)	83 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T19 [T 19mm]

# MASTERColour CDM-T Fresh

Approval and Application	
Mercury (Hg) Content (Nom)	6 mg
Energy Consumption kWh/1000 h	80 kWh
Product Data	
Order product name	MASTERColour CDM-T Fresh 70W/740 G12 1CT
Full product name	MASTERColour CDM-T Fresh 70W/740 G12 1CT
Full product code	87182911254000


Order code	928196405131
Material Nr. (12NC)	928196405131
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291125440
Numerator - Packs per outer box	12
EAN/UPC - Case	8718291125457

## Dimensional drawing




Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERColour CDM-T Fresh 70W/740 G12 1CT	20 mm	7.15 mm	55 mm	57 mm	56 mm	103 mm

## Photometric data




Light Distribution Diagram - MASTERColour CDM-T Fresh 70W/740 G12 1CT



Spectral Power Distribution Colour - MASTERColour CDM-T Fresh 70W/740 G12 1CT

MASTERColour CDM-T Fresh

Lifetime



Life Expectancy Diagram - MASTERColour CDM-T Fresh 70W/740 G12 1CT

Lumen Maintenance Diagram - MASTERColour CDM-T Fresh 70W/740 G12 1CT

