



HORTI

MASTER GreenPower CG T 250W E40 1SL/12

High Pressure Sodium lamp with clear outer bulb, optimized growthlight output and maintenance

Warnings and Safety


- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	E40
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	32,000 hour(s)
Light Technical	
Color Code	220 [CCT of 2000K]
Correlated Color Temperature (Nom)	2000 K
Luminous Efficacy (rated) (Nom)	122 lm/W
Color rendering index (CRI)	29
Arc Length O (Nom)	94.2 mm
Operating and Electrical	
Power Consumption	265.0 W
Voltage (Nom)	114 V
Voltage (Nom)	114 V
Controls and Dimming	
Dimmable	Yes


Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	T46
Approval and Application	
Mercury (Hg) Content (Nom)	15.1 mg
Energy Consumption kWh/1000 h	292 kWh
Product Data	
Order product name	MASTER GreenPower CG T 250W E40 1SL/12
Full product name	MASTER GreenPower CG T 250W E40 1SL/12
Full product code	872790085775700
Order code	928197109227
Material Nr. (12NC)	928197109227
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900857757
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900857764

Dimensional drawing




Product	D (max)	O	L	C (max)	A
MASTER GreenPower CG T 250W E40 1SL/12	47 mm	94.2 mm	158 mm	257 mm	170 mm

Photometric data




Light Distribution Diagram - MASTER GreenPower CG T 250W E40 1SL/12

Lifetime



Life Expectancy Diagram - MASTER GreenPower CG T 250W E40 1SL/12



Lumen Maintenance Diagram - MASTER GreenPower CG T 250W E40 1SL/12

