



MASTER SON-T APIA Plus Hg Free

MST SON-T APIA Plus Hg Free 100W E40 1SL

High-pressure sodium lamp with clear tubular outer bulb, long reliable lifetime and zero mercury

Warnings and Safety

- Control gear must include end-of-life protection (IEC 60662, IEC 62035)


Product data

General Information	
Cap-Base	E40 [E40]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	38,000 hour(s)
Light Technical	
Color Code	- [Not Specified]
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Arc Length O (Nom)	71 mm
Operating and Electrical	
Power Consumption	100.0 W
Voltage (Nom)	95 V
Voltage (Nom)	95 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear

Bulb Shape	T46 [T 46mm]
Approval and Application	
Mercury (Hg) Content (Nom)	0 mg
Energy Consumption kWh/1000 h	110 kWh
Product Data	
Order product name	MST SON-T APIA Plus Hg Free 100W E40 1SL
Full product name	MST SON-T APIA Plus Hg Free 100W E40 1SL
Full product code	872790088075500
Order code	928198909830
Material Nr. (12NC)	928198909830
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900880755
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900880762



MASTER SON-T APIA Plus Hg Free

Dimensional drawing



Product	D (max)	O	L	C (max)
MST SON-T APIA Plus Hg Free 100W E40 1SL	47 mm	71 mm	132 mm	210 mm


Photometric data



Light Distribution Diagram - MST SON-T APIA Plus Hg Free 100W E40 1SL

Spectral Power Distribution Colour - MST SON-T APIA Plus Hg Free 100W E40 1SL

Lifetime



Lumen Maintenance Diagram - MST SON-T APIA Plus Hg Free 100W E40 1SL

Life Expectancy Diagram - MST SON-T APIA Plus Hg Free 100W E40 1SL

MASTER SON-T APIA Plus Hg Free

