



# **MASTER HPI-T Plus**

## MASTER HPI-T Plus 400W/645 E40 1SL/12

Quartz metal halide lamps with clear outer bulb

#### Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- For use with control gear designed for high-pressure mercury or sodium lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information					
Cap-Base	E40 [E40]				
Operating Position	P20 [Parallel +/-20D or Horizontal(HOR)]				
Life to 50% Failures (Nom)	20,000 hour(s)				
Light Technical					
Color Code	645 [CCT of 4500K]				
Color Designation	Cool White (CW)				
Chromaticity Coordinate X (Nom)	361				
Chromaticity Coordinate Y (Nom)	372				
Correlated Color Temperature (Nom)	4500 K				
Luminous Efficacy (rated) (Nom)	83 lm/W				
Color rendering index (CRI)	65				
Arc Length O (Nom)	30.5 mm				
Operating and Electrical					
Power Consumption	385 W				
Voltage (Nom)	125 V				

Voltage (Nom)	125 V				
Controls and Dimming					
Dimmable	No				
Mechanical and Housing					
Bulb Finish	Clear				
Bulb Shape	T46 [T 46mm]				
Approval and Application					
Mercury (Hg) Content (Nom)	29.5 mg				
Energy Consumption kWh/1000 h	424 kWh				
Product Data					
Order product name	MASTER HPI-T Plus 400W/645 E40 1SL/12				
Full product name	MASTER HPI-T Plus 400W/645 E40 1SL/12				
Full product code	692234199963500				
Order code	928481600094				


Datasheet, 2023, September 22 data subject to change

## **MASTER HPI-T Plus**

Material Nr. (12NC)	928481600094
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6922341999635
Numerator - Packs per outer box	12


EAN/UPC - Case	6922341993244


## Dimensional drawing




Product	D (max)	0	L	C (max)
MASTER HPI-T Plus 400W/645 E40 1SL/12	47 mm	30.5 mm	168 mm	286 mm

#### Photometric data









Light Distribution Diagram - MASTER HPI-T Plus 400W/645 E40 1SL/12

Spectral Power Distribution Colour - MASTER HPI-T Plus 400W/645 E40 1SL/12

### Lifetime





Life Expectancy Diagram - MASTER HPI-T Plus 400W/645 E40 1SL/12

Lumen Maintenance Diagram - MASTER HPI-T Plus 400W/645 E40 1SL/12

## **MASTER HPI-T Plus**



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.