

MHN-TD

MHN-TD 70W/730 RX7s 1CT/12

Double-envelope, single- or double-ended Metal halide lamps

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	RX7S [RX7s]
Operating Position	P45 [Parallel +/-45D or Horizontal(HOR)]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	9,000 hour(s)

Light Technical	
Color Code	730 [CCT of 3000K]
Luminous Flux	5,800 lm
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.434
Chromaticity Coordinate Y (Nom)	0.398

Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (Rated) (Min)	67 lm/W
Luminous Efficacy (rated) (Nom)	75 lm/W
Color rendering index (CRI)	65
Arc Length O (Nom)	7.7 mm

Operating and Electrical	
Power Consumption	77.0 W
Voltage (Nom)	90 V
Voltage (Nom)	90 V

MHN-TD


Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	TD

Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	13.4 mg
Mercury (Hg) Content (Nom)	13.4 mg
Energy Consumption kWh/1000 h	77 kWh
EPREL Registration Number	473286


Product Data	
Order product name	MHN-TD 70W/730 RX7s 1CT/12
Full product name	MHN-TD 70W/730 RX7s 1CT/12
Full product code	871829121530100
Order code	928482400092
Material Nr. (12NC)	928482400092
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291215301
Numerator - Packs per outer box	12
EAN/UPC - Case	8718291215318

Dimensional drawing




Product	D (max)	D	O	C (max)
MHN-TD 70W/730 RX7s 1CT/12	19.5 mm	0.75 inch	7.7 mm	117.6 mm

Photometric data



Light Distribution Diagram - MHN-TD 70W/730 RX7s 1CT/12



Spectral Power Distribution Colour - MHN-TD 70W/730 RX7s 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.